

End Finishes

Industrial Ventilation Ducting



ATTACHED BELT CUFF

Belt cuffs are fabricated using 1" (25 mm) polyester webbing and finished with nickel-plated buckles. Available in all diameters of EnviroDuct®, AirVent™ and ThermoHose®.



ATTACHED SOFT CUFF

The soft cuff is comprised of two pieces of appropriate fabric that are attached to a standard ducting end. This additional fabric provides extra coupling flexibility for a variety of attachments. Note: Each soft cuff adds 3" (7.5 cm) to the total ducting length.



ZIPPER CUFF

Zipper cuffs are manufactured by sewing one side of a zipper assembly to the first duct at a connection point. The cuff on the second duct contains the coordinating zipper teeth to form a secure union. Velcro® adds a second layer of protection against unwanted dust and debris at ducting connection points. The resulting connection features an overlapping female entry and male exit.



WIRE ROPE COUPLING

Wire rope couplings join ducting sections by inserting one ducting section with the wire rope coupling into another with the same coupling. This union provides a secure fit and extended service life. Wire rope couplings may be used in conjunction with multi-clips and are available in 6" (150 mm) or larger sizes.



INTEGRAL SCREW CLAMP CUFF

Screw clamp cuffs are ideal for securing ducting to heaters, blowers, A/C, or dehumidification units without the hassle of attaching an exterior clamp. Featuring a sewn-in, stainless steel clamp, the ducting is secured by screwing the hardware to the desired tightness.



T-BOLT BAND CLAMP CUFF

T-Bolt band clamps provide high tensile strength, durability, and corrosion resistance, therefore ideal for medium and heavy-duty applications. Featuring a sewn-in, stainless steel clamp, the ducting is secured by screwing the hardware to the desired tightness.



ALUMINUM OR STAINLESS STEEL SLEEVES

Stainless steel or aluminum sleeves are ideal for joining ducting sections that need a durable, uniform connection. The sleeves may be used in conjunction with a flat band clamp or screw clamp and are available in 4" to 30" (100 to 750 mm) diameters.

ABC INDUSTRIES, INC.

P.O. Box 77, Warsaw, IN 46581-0077

800.426.0921 Toll-Free

574.267.5166 Phone

574.267.2045 Fax

sales@abc-industries.net

www.abc-industries.net

