
ADH-8000

A fully portable dehumidifier providing fast drying

This unit is utilized by restoration rental companies and industrials for building drying, process drying, and general dehumidification.

AIRREX Large Capacity Dehumidifier **Features**



Digital Controls

- Off Timer: 24hr
- Adjustable 2-Step Fan Speed
- Error Messaging
- · Current and Set Humidity Display

Built-in Replaceable Drain Pump

 Powerful Automatic Drain Pump

Excellent Defrost

Hot Gas Bypass

Forced Drainage

 Before moving the dehumidifier, push this button not to overflow the remaining condensed water

















ADH-8000 Specifications

ITEMS	Dehumidifier			
Power Supply	115V~ 60Hz 1Ph			
Dehumidification	MAX. 25.4gal/day			day
	NOMINAL 15.9gal/day			day
Power Consumption	1.17 kW			
Current Consumption	10.25 A			
Refrigerant	R-410A / 1.43 lbs			
Decibel Level	60 dB			
Motor Compressor	RLA	8.5A	LRA	38A
Motor	FLA	2.1A	HP	0.32A
High Pressure	441 psi			
Low Pressure	128 psi			
Dimensons (WxDxH)	20 x 20 x 33.5 inch			
Weight	118 lbs			
Operating Temp	34°F ~ 100°F (1~38°C)			
Air Flow	High 554 CFM / Low 392 CFM (1 year warranty and 3 years on compressor)			



^{*} Designs and specifications of products are subject to change without prior notice for the improvements. The colors of products may be different due to the printing process.

Ideal applications for Airrex Dehumidifier.













Flood restoration, building, process drying and general dehumidification, etc.







