

HSC-18

AIRREX PORTABLE AIR CONDITIONER



Cool Solutions by Airrex! Approved technology with 30 years experience in the Market! Airrex Spot Cooler 1.5-Ton

Airrex spot coolers operate in air temperatures from 65° to 113°F. These air conditioners utilize eco-friendly 410A refrigerant. Airrex spot cooler air conditioners may require a fresh air supply for proper operation. Includes removable, washable air filters for easy maintenance. Thermostatically protected compressor includes high and low pressure warnings. Moves easily on swivel casters (2 locking). 16,800 BTU Cooling feature 5" diameter front cold air discharge and 12" diameter top warm air discharge. Optional Warm Air Duct includes 8'L ducting and a 2' x 2' ceiling flange for warm air exhausting. ETL listed. Optional Condensate Pump that plugs directly into the portable air conditioner. 1 Year Warranty. 3 Year LG compressor warranty



Hot Air Exhaust

Automatic Fan Speed Controller
Operating Range : Up to 113°F



Twist & Lock

(2)5"x14"
Easy to disassemble & store



Spot Cooling

Directed Cooling
16,800BTU



Mobility

(4) 4" Swivel Casters
(2) Locking Casters



Condensate Tank

5 Gallon Tank Auto Shut off



Applications

Indoor or Outdoor
Cooling Drying



Digital Controls

Programmable Timer
Temperature Range: 64°F to 86°F
High/Low Fan Speed
Auto Restart



LCDI Protection

LCDI Recessed Power Cords
Standard 115 Volt Power
ETL Certified

Strong Point



Quiet



Thermostats



Intensive
air Conditioning



Movable & Lockable



Fuel savings



automatic



Time Settings



Certification

HSC-18 Specifications

Items	Unit	HSC-18
Cooling capacity	BTU/h	16,800
Power Supply	Volts	115Vac 60Hz 1Ph
Size (WDXH)	inch.	19.3 X 23.6 X 49.8
Weight	lbs	185
Current Consumption (AMPS)	A	17
Circuit Breaker Size (AMPS)	A	20
Rated Power Consumption (Cooling)	kW	1.95
Compressor Input	kW	1.45
Air Flow (CMP,High/Low)Evaporator	CFM	460 / 400
Air Flow(CMP,High/Low)Condenser	CFM	920
Motor Input	kW	0.38
Air Filter	-	Aluminum Filter
Nema Plug	-	5 - 20
Safety Device		<ul style="list-style-type: none"> • High/Low Pressure Switch • Automatic Full Tank Shut-Off • Tank Position Detector(only HSC-14/18/24A) • Fan Motor Protection • Thermostat Protector for Compressor • 3min, Delay Timer
Power Cord	type	PLUG TYPE
Power Cord Length	ft	9.8
Refrigerant	lbs	R-410A (1.76)
Operating Conditions	°F	65°F DB 60%RH~113°F DB 40%RH
Maximum Duct Length	ft	30
Static Pressure	psi	0.042
Outlet Air Velocity	ft/sec	38~33
Outlet Temp. Difference	°F	50~59
Condensate pump	-	Optional
Dehumidification in gallon per day		19(gal/day) / 89.6°F 80% (MAX.) ~ 13.3(gal/day) / 80.6°F 60% (AHAM)

※ Designs and specifications of products are subject to change without prior notice for the improvements. The colors of products may be different due to the printing process.

Ideal Applications for Airrex Portable Air Conditioner



Industrial Sites High Temperature work sites, Car manufacturing plants, Ship building yards and steel mills

Repair Shops Car repair shops, Aircraft workshops, Farm machinery workshops, Gas stations & parking facilities

Heat Generating Equipment Server rooms and machine rooms

Leisure / Outdoor Event Venues, Farm & Livestock Ranges

Airrex USA Office Mailing Address:
1191 Jewell Dr Ste 101, Waco, TX 76712

TEL: 888-535-8841
FAX: 469-574-7924

E-mail: sales@airrexusa.com
Website: www.airrexusa.com