

Bray Controls Commercial Division 13788 West Road, Suite 200A Houston, Texas 77041

BCDSales@Bray.com Phone: 1-888-412-2729 Fax: 1-888-412-2720

www.braycommercialdivision.com

Butterfly Retrofit Form

02/02/15

SECTION - 1	SECTION - 2	SECTION - 3
Quantity	Mounting Style (A2, B2, or C2 below)	Shaft Style (A3, B3, C3, or E3 below):
Nominal Valve Size	Dimensions: A = (in.)	Dimensions: D =(in.)
Valve Manufacturer (if known)	B = (in.)	E =(in.)
Model No. (if known)	C = (in.)	F =(in.)
Valve Style:	Are Mounting Holes Drilled and Tapped:	G =(in.)
	No, Hole Diameter	H =(in.)
2-Way or 3-Way	Yes, Bolt SizeThreads/inch	Note: Dimension F_(for keywayed, flatted, or
ACTUATION: (Check all that apply)	ADDITIONAL COMMENTS	pinned) is it perpendicular or parallel to disc.
On/Off Tri-State Modulating		
Spring Return		
☐ 24VAC ☐ 120VAC		
■ Weather Proof Enclosure		
Approximate Torque Required (in-lbs.)	ル <i>ーーーー)</i>	

Mounting and shaft styles

