

Bray Controls Commercial Division 13788 West Road, Suite 200A Houston, Texas 77041

BCDSales@Bray.com Phone: 1-888-412-2729 Fax: 1-888-412-2720

www.braycommercialdivision.com

VA24-35-P — Submittal/Technical Data

02/07/19

35 lb-in. — Non-Spring Return — Floating — Plenum Cable

Specifications:

Power Supply Operating Voltage 24 VAC +25%/-20% at 50/60 Hz

Power Consumption 2.1 VA

Equipment Rating Class 2 or Safety Extra-Low Voltage (SELV)

Control Signal Input Signal 24 VAC +25%/-20% at 50/60 Hz, Class 2 or SELV

Function Torque 35 in-lbs. (4 Nm)

Runtime for 90° of Rotation 60 Seconds at 60 Hz / 72 Seconds at 50 Hz

Rotation Range 93° ±3°, CW or CCW

Mounting Shaft Size Up to 1/2 in. (13 mm) Diameter Round Shaft or 3/8 in. (10 mm) Square Shaft

Enclosure NEMA 2, IP42

Manual Override External Push Button

Ambient Conditions/Temperatures

Operating -4 to 140°F (-20 to 60°C); 90% RH Maximum, Non-Condensing Storage -20 to 150°F (-29 to 66°C); 90% RH Maximum, Non-Condensing

Connection 48 in. (1.2 m) UL 444 Type CMP Plenum Rated Cable with 19 AWG (0.75 mm2)

conductors and 1/4 in. (6 mm) ferrule ends

Life Cycle 100,000 Full Stroke Cycles; 2,500,000 repositions at rated running torque

Audible Noise Rating 35 dBA Nominal at 1 Meter

Dimensions Actuator Only - (L) 5.16"x (W) 2.81"x (H) 2.06

Weight 1.25 lb. (0.55 kg)

Agency Certification United States UL Listed, File E27734, CCN XAPX (United States) and XAPX7 (Canada)

Actuator Housing is Plenum Rated per CSA C22.2 No. 236/UL 1995,


Heating and Cooling Equipment

Europe CE Mark - Product is in compliance with the essential requirements

and other relevant provisions of the EMC Directive 2004/108/EC.

Australia and New Zealand C-Tick Mark Australia/NZ Emissions Compliant

Wiring: (Plenum Cable)



NOTE: To avoid excessive wear or drive time on the motor, use a controller and/or software that provides a time-out function to remove the signal at the end of rotation (stall).

The performance specifications are nominal and conform to acceptable industry standards. For application at conditions beyond these specifications, consult the nearest Bray office. Bray controls shall not be liable for damages resulting from misapplication or misuse of its products.