



DU97 Bridge Ducting

**Application:**

Manufactured with high-strength PVC reinforced polyester fabric. Constructed with bi-directional air-flow, continuous heavy-duty high-tensile wire helix, and abrasion resistant wear-strip. Recommended for negative pressure (suction) dust collecting applications. Ideal for: Sand-blasting, painting, bridge restoration, shipyard ventilation, industrial tanks, vessels, and more.

Features:

- PVC reinforced wear-strip.
- Low profile.
- 166% stronger adhesions than comparable products.
- Best weight to strength ratio in the industry.

Construction:

Tube - Passes NFPA 701 (large scale) and California Fire Marshal Title 19 (para 1237.1). Phthalate Free

Reinforcement - Heavy-duty reinforced PVC extruded fabric with industry leading heat-sealing technology

Part No.	Hose Size & Length	Type	Max Temp.	Pitch	Grommeted/ Non-Grommeted	Body Color/ Wear Strip
DU97-1225BB	12" x 25'	Bridge Duct	180°F	2"	Non-Grommeted	Black/Black
DU97-1825BB	18" x 25'	Bridge Duct	180°F	2"	Non-Grommeted	Black/Black
DU97-2025BB	20" x 25'	Bridge Duct	180°F	2"	Non-Grommeted	Black/Black
DU97-2425BB	24" x 25'	Bridge Duct	180°F	2"	Non-Grommeted	Black/Black