



PE09 Smooth Oilfield Vacuum Hose



Application:

Not to be used for refined products above 30% aromatic content. Tank truck service, including oil field vacuum truck, where full suction or rated working pressures are required. Ideal for applications handling crude oil, salt and fresh water, tank bottoms, drilling mud, dilute solutions of hydrochloric acids, diesel fuels, and sewage transfer.

NOTE: Not recommended for refined petroleum products such as gasoline.

Tube - Black smooth synthetic rubber compound, ARPM Class C

Reinforcement - Synthetic yarn with a steel spiral wire helix

Cover - Black, smooth finish, synthetic rubber cover; oil, fuel, weather and ozone resistant

Branding - FLEXTRAL PE09-200 2" OILFIELD VACUUM 150 PSI MAX WP

Temperature Range:

-30°C to +85°C (-20°F to +185°F)

Part No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Bend Radius Inches	Weight lbs / ft	Standard Lengths
PE09-200	2	2.44	150	8.0	1.04	200'
PE09-300	3	3.46	150	12.0	1.74	200'
PE09-400	4	4.57	150	16.0	2.55	200'

****Caution:** Static wire must be properly grounded during fabrication and tested to ensure static continuity of hose assemblies.

PE09 Smooth Oilfield Vacuum Hose Assemblies



Part No.	Hose Size & Length	End 1	End 2	Attaching Method
PE09-200CEX020-AL	2" X 20'	Fem Cam Alum.	Male Cam Alum.	Crimp Sleeve
PE09-300CEX020-AL	3" X 20'	Fem Cam Alum.	Male Cam Alum.	Crimp Sleeve
PE09-400CEX020-AL	4" X 20'	Fem Cam Alum.	Male Cam Alum.	Crimp Sleeve



Part No.	Hose Size & Length	End 1	End 2	Attaching Method
PE09-200MMX020-AL	2" X 20'	M-NPT	M-NPT	Crimp Sleeve
PE09-300MMX020-AL	3" X 20'	M-NPT	M-NPT	Crimp Sleeve
PE09-400MMX020-AL	4" X 20'	M-NPT	M-NPT	Crimp Sleeve

*Call for additional fittings, lengths and assemblies.