



SuperJet6000 6000 PSI Pressure Washer Hose



- Tube:** Seamless, black synthetic rubber
Reinforcement: Two braids of high-tensile steel wire
Cover: Wrapped or Smooth abrasion and weather resistant synthetic rubber, Black, Blue or Gray
Temperature: -40°C to +121°C/149°C Intermittent (-40°F to +250°F/300°F Intermittent)
Packaging: 50', 100', 150', 200' in Bulk Reels
Application: Pressure wash equipment. All of the hose assemblies shown here are factory made with male NPT end fittings and bend restrictors at each end. One male end is a swivel to prevent hose twisting.
NOT FOR STEAM SERVICE.

PART NUMBER	COVER	HOSE I.D.	HOSE O.D.		MAX W.P.	MIN. BEND RADIUS		WEIGHT (lbs/ft)	ONE PIECE
		(in)	(in)	(mm)		(psi)	(in)		(mm)
SJ6-06BK	Wrapped	3/8	0.67	17.02	6,000	3.5	88.9	0.29	E
SJ6-06GY	Wrapped	3/8	0.67	17.02	6,000	3.5	88.9	0.29	E
SJ6-06BLM	Smooth	3/8	0.67	17.02	6,000	3.5	88.9	0.29	E

*BK indicates the color Black. For other colors add the suffix to the part number as follows:
 GY - Gray, BLM - Blue (Smooth Only).

*6,000 PSI assemblies come with Red bend restrictors.

SUPERJET® 6000 6000 PSI Assemblies

PART NUMBER	COLOR	COVER	HOSE SIZE & LENGTH	END 1	END 2	ATTACHING METHOD
SJ6-06BK-050C	Black	Wrapped	3/8" x 50'	3/8" M-NPT Rigid	3/8" M-NPT Swivel	Crimp
SJ6-06BK-100C	Black	Wrapped	3/8" x 100'	3/8" M-NPT Rigid	3/8" M-NPT Swivel	Crimp
SJ6-06GY-050C	Gray	Wrapped	3/8" x 50'	3/8" M-NPT Rigid	3/8" M-NPT Swivel	Crimp
SJ6-06GY-100C	Gray	Wrapped	3/8" x 100'	3/8" M-NPT Rigid	3/8" M-NPT Swivel	Crimp
SJ6-06BLM-050C	Blue	Smooth	3/8" x 50'	3/8" M-NPT Rigid	3/8" M-NPT Swivel	Crimp
SJ6-06BLM-100C	Blue	Smooth	3/8" x 100'	3/8" M-NPT Rigid	3/8" M-NPT Swivel	Crimp

*6,000 PSI assemblies come with Red bend restrictors.

*Call for additional fittings, lengths and assemblies.

