




## WA10 Blue PVC Layflat



### Application:

A standard duty hose for portable pump and irrigation use. Hose folds flat for ease of coiling and handling. Common applications are rental, construction, mining, dewatering, agricultural, and marine service.

### Construction:

**Tube** - PVC

**Reinforcement** - Woven synthetic yarn

**Cover** - Blue, PVC

**Branding** - FLEXTRAL WA10-200 80 PSI MAX WP

### Temperature Range:

-21°C to +54°C (-5°F to +130°F)

Part No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Weight lbs / ft	Standard Lengths
WA10-100	1	1.11	85	0.11	300'
WA10-125	1¼	1.36	85	0.12	300'
WA10-150	1½	1.61	85	0.14	300'
WA10-200	2	2.11	80	0.20	300'
WA10-250	2½	2.62	70	0.27	300'
WA10-300	3	3.13	70	0.34	300'
WA10-400	4	4.13	70	0.48	300'
WA10-600	6	6.14	50	0.77	300'
WA10-800	8	8.15	50	1.21	300'
WA10-1000	10	10.12	35	1.81	100'
WA10-1200	12	12.13	30	1.95	100'

## WA10 Blue PVC Layflat Assemblies



Part No.	Hose Size & Length	End 1	End 2	Attaching Method
WA10-200CE050-AL	2" x 50'	Fem Cam Alum.	Male Cam Alum.	Preformed Band
WA10-300CE050-AL	3" x 50'	Fem Cam Alum.	Male Cam Alum.	Preformed Band
WA10-400CE050-AL	4" x 50'	Fem Cam Alum.	Male Cam Alum.	Preformed Band
WA10-600CE050-AL	6" x 50'	Fem Cam Alum.	Male Cam Alum.	Preformed Band
WA10-800CE050-AL-__*	8" x 50'	Fem Cam Alum. - 1 or 2	Male Cam Alum. - 1 or 2	Preformed Band

\*Specify (N)=Type 1 for NECO Style or (P)=Type 2 for PT Style. See Page 174 for Detailed Type Explanation.



Part No.	Hose Size & Length	End 1	End 2	Attaching Method
WA10-150MFIPT050-AL	1½" x 50'	M-NPSM	F-NPSM	Preformed Band
WA10-200MFIPT050-AL	2" x 50'	M-NPSM	F-NPSM	Preformed Band
WA10-300MFIPT050-AL	3" x 50'	M-NPSM	F-NPSM	Preformed Band
WA10-400MFIPT050-AL	4" x 50'	M-NPSM	F-NPSM	Preformed Band

\*Call for additional fittings, lengths and assemblies.