



## WA12 Gray PVC Layflat



**Application:**

A standard duty hose for portable pump and irrigation use. Hose folds flat for ease of coiling and handling. Common applications are rental, construction, mining, agricultural, and marine service.

**Construction:**

**Tube** - PVC

**Reinforcement** - Woven synthetic yarn

**Cover** - Gray, PVC

**Temperature Range:**


-23°C to +66°C (-10°F to +150°F)

Part No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Weight lbs / ft	Standard Lengths
WA12-150	1½	1.73	90	0.19	300'
WA12-200	2	2.22	80	0.24	300'
WA12-250	2½	2.79	60	0.36	300'
WA12-300	3	3.31	50	0.39	300'
WA12-400	4	4.33	45	0.65	300'
WA12-600	6	6.38	35	1.07	300'

## WA12 Gray PVC Layflat Assemblies



Part No.	Hose Size & Length	End 1	End 2	Attaching Method
WA12-150CE050-AL	1½" X 50'	Fem Cam Alum.	Male Cam Alum.	Preformed Band
WA12-200CE050-AL	2" x 50'	Fem Cam Alum.	Male Cam Alum.	Preformed Band
WA12-300CE050-AL	3" x 50'	Fem Cam Alum.	Male Cam Alum.	Preformed Band
WA12-400CE050-AL	4" x 50'	Fem Cam Alum.	Male Cam Alum.	Preformed Band
WA12-600CE050-AL	6" x 50'	Fem Cam Alum.	Male Cam Alum.	Preformed Band



Part No.	Hose Size & Length	End 1	End 2	Attaching Method
WA12-150MFIPT050-AL	1½" X 50'	M-NPSM	F-NPSM	Preformed Band
WA12-200MFIPT050-AL	2" x 50'	M-NPSM	F-NPSM	Preformed Band
WA12-300MFIPT050-AL	3" x 50'	M-NPSM	F-NPSM	Preformed Band
WA12-400MFIPT050-AL	4" x 50'	M-NPSM	F-NPSM	Preformed Band

\*Call for additional fittings, lengths and assemblies.