



## WA14 HD Brick Red PVC Layflat



**Application:**

A heavy-duty hose for portable pump and irrigation use. Hose folds flat for ease of coiling and handling. Common applications are rental, construction, mining, agricultural and marine service.

**Construction:**

**Tube** - PVC

**Reinforcement** - Woven synthetic yarn

**Cover** - Brick Red, PVC

**Branding** - FLEXTRAL WA14-300 150 PSI MAX WP

**Temperature Range:**

-21°C to +54°C (-5°F to +130°F)

Part No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Weight lbs / ft	Standard Lengths
WA14-200	2	2.21	150	0.28	300'
WA14-300	3	3.25	150	0.48	300'
WA14-400	4	4.35	150	0.76	300'
WA14-600	6	6.36	115	1.17	300'
WA14-800	8	8.35	75	1.54	300'

## WA14 HD Brick Red PVC Layflat Assemblies



Part No.	Hose Size & Length	End 1	End 2	Attaching Method
WA14-200CE050-AL	2" x 50'	Fem Cam Alum.	Male Cam Alum.	Preformed Band
WA14-300CE050-AL	3" x 50'	Fem Cam Alum.	Male Cam Alum.	Preformed Band
WA14-400CE050-AL	4" x 50'	Fem Cam Alum.	Male Cam Alum.	Preformed Band
WA14-600CE050-AL	6" x 50'	Fem Cam Alum.	Male Cam Alum.	Preformed Band
WA14-800CE050-AL-__*	8" x 50'	Fem Cam Alum. - 1 or 2	Male Cam Alum. - 1 or 2	Preformed Band

\*Specify (N)=Type 1 for NECO Style or (P)=Type 2 for PT Style. See Page 174 for Detailed Type Explanation.



Part No.	Hose Size & Length	End 1	End 2	Attaching Method
WA14-200MFIPT050-AL	2" x 50'	M-NPSM	F-NPSM	Preformed Band
WA14-300MFIPT050-AL	3" x 50'	M-NPSM	F-NPSM	Preformed Band
WA14-400MFIPT050-AL	4" x 50'	M-NPSM	F-NPSM	Preformed Band

\*Call for additional fittings, lengths and assemblies.