



WA22 Yellow Iron River Standard Duty



Application:

A premium high-pressure PVC/nitrile layflat hose, suited ideally for mining, construction, agriculture, water jetting, dewatering, industrial wash down, submersible pump discharge applications. This hose has excellent abrasion and weathering resistance and limited oil resistance.

Construction:

Tube - Yellow, abrasion and oil resistant nitrile / PVC

Reinforcement - One-piece through the weave

Cover - Yellow, ribbed abrasion, weather and oil resistant nitrile / PVC

Branding - FLEXTRAL WA22-200 2" 300 PSI MAX WP

Temperature Range:

-46°C to +80°C (-50°F to +176°F)

| Part No. | I.D. Inches | O.D. Inches | Max W.P. PSI | Weight lbs / ft | Standard Lengths |
|----------|-------------|-------------|--------------|-----------------|------------------|
| WA22-200 | 2 | 2.25 | 300 | 0.31 | 50'/100' |
| WA22-300 | 3 | 3.35 | 250 | 0.53 | 50'/100' |
| WA22-400 | 4 | 4.35 | 200 | 0.72 | 50'/100' |
| WA22-600 | 6 | 6.39 | 150 | 1.17 | 50'/100' |
| WA22-800 | 8 | 8.47 | 150 | 2.08 | 50'/100' |

WA22 Yellow Iron River Assemblies



| Part No. | Hose Size & Length | End 1 | End 2 | Attaching Method |
|----------------------|--------------------|------------------------|-------------------------|------------------|
| WA22-200CEX050-AL | 2" x 50' | Fem Cam Alum. | Male Cam Alum. | Crimp Sleeve |
| WA22-300CEX050-AL | 3" x 50' | Fem Cam Alum. | Male Cam Alum. | Crimp Sleeve |
| WA22-400CEX050-AL | 4" x 50' | Fem Cam Alum. | Male Cam Alum. | Crimp Sleeve |
| WA22-600CEX050-AL | 6" x 50' | Fem Cam Alum. | Male Cam Alum. | Crimp Sleeve |
| WA22-800CEX050-AL-_* | 8" x 50' | Fem Cam Alum. - 1 or 2 | Male Cam Alum. - 1 or 2 | Crimp Sleeve |

*Specify (N)=Type 1 for NECO Style or (P)=Type 2 for PT Style. See Page 174 for Detailed Type Explanation.



| Part No. | Hose Size & Length | End 1 | End 2 | Attaching Method |
|-------------------|--------------------|---------------|-----------------|------------------|
| WA22-200BSIX050-B | 2" x 50' | Ball - Type B | Socket - Type B | Crimp Sleeve |
| WA22-300BSIX050-B | 3" x 50' | Ball - Type B | Socket - Type B | Crimp Sleeve |
| WA22-400BSIX050-B | 4" x 50' | Ball - Type B | Socket - Type B | Crimp Sleeve |
| WA22-600BSIX050-B | 6" x 50' | Ball - Type B | Socket - Type B | Crimp Sleeve |
| WA22-800BSIX050-B | 8" x 50' | Ball - Type B | Socket - Type B | Crimp Sleeve |

*Call for additional fittings, lengths and assemblies.