



WA35 Single Jacket - Industrial Mill Discharge



Application:

Heavy-duty pump discharge and washdown hose, lightweight, and layflat. Not approved for fire fighting service.

Construction:

Tube - Synthetic rubber blend

Cover - Single jacket, white 100% polyester

Temperature Range:

-17°C to +82°C (0°F to +180°F)

Part No.	I.D. Inches	Max W.P. PSI	Burst Pressure Max PSI	Weight lbs / ft	Standard Lengths
WA35-150	1½	150	450	0.14	50'/100'
WA35-200	2	150	450	0.20	50'/100'
WA35-250	2½	150	450	0.26	50'/100'
WA35-300	3	150	450	0.32	50'/100'
WA35-400	4	150	450	0.50	50'/100'
WA35-600	6	150	450	1.08	50'

WA35 Industrial Mill Discharge Assemblies

Single Jacket Mill Hose



Part No.	Hose Size & Length	Fitting Material	End 1	End 2	Attaching Method
WA35-150NPSE050-AL	1½" x 50'	Alum.	M-NPSH	F-NPSH	Expanded
WA35-150NSTER050-AL	1½" x 50'	Alum.	M-NST	F-NST	Expanded
WA35-200NPSE050-AL	2" x 50'	Alum.	M-NPSH	F-NPSH	Expanded
WA35-200CE050-AL	2" x 50'	Alum.	Male Cam	Fem Cam	Preformed Band
WA35-200CE100-AL	2" x 100'	Alum.	Male Cam	Fem Cam	Preformed Band
WA35-250NPSE050-AL	2½" x 50'	Alum.	M-NPSH	F-NPSH	Expanded
WA35-250NSTER050-AL	2½" x 50'	Alum.	M-NST	F-NST	Expanded
WA35-300MFIPT050-AL	3" x 50'	Alum.	M-NPSH	F-NPSH	Preformed Band
WA35-300CE050-AL	3" x 50'	Alum.	Male Cam	Fem Cam	Preformed Band
WA35-300CE100-AL	3" x 100'	Alum.	Male Cam	Fem Cam	Preformed Band
WA35-400MFIPT050-AL	4" x 50'	Alum.	M-NPSH	F-NPSH	Preformed Band

*Call for additional fittings, lengths and assemblies.