



WA38 Double Jacket - Industrial Mill Discharge



Application:

Heavy-duty pump discharge and washdown hose, lightweight, and layflat. Not approved for fire fighting service.

Construction:

Tube - Synthetic rubber blend

Cover - Double jacket white 100% polyester

Temperature Range:

-17°C to +82°C (0°F to +180°F)

Part No.	I.D. Inches	Max W.P. PSI	Burst Pressure Max PSI	Weight lbs / ft	Standard Lengths
WA38-150	1½	250	750	0.26	50'/100'
WA38-250	2½	250	750	0.47	50'/100'
WA38-300	3	250	750	0.57	50'/100'
WA38-400	4	250	750	0.79	50'/100'

WA38 Industrial Mill Discharge Assemblies

Double Jacket Mill Hose



Part No.	Hose Size & Length	Fitting Material	End 1	End 2	Attaching Method
WA38-150NPSE050-AL	1½" x 50'	Alum.	M-NPSH	F-NPSH	Expanded
WA38-150NSTE050-AL	1½" x 50'	Alum.	M-NST	F-NST	Expanded
WA38-250NPSE050-AL	2½" x 50'	Alum.	M-NPSH	F-NPSH	Expanded
WA38-250NSTE050-AL	2½" x 50'	Alum.	M-NST	F-NST	Expanded

*Call for additional fittings, lengths and assemblies.