



WA50 HD Rubber Suction & Discharge



Application:

A heavy-duty rubber suction hose for construction, quarries, mining, dewatering, heavy-duty applications, and general use. Suitable for full vacuum.

Construction:

Tube - Black, smooth rubber

Reinforcement - Synthetic yarn with a wire helix

Cover - Black, weather, and abrasion resistant rubber

Branding - FLEXTRAL WA50-200 2" RUBBER WATER SUCTION HOSE 150 PSI MAX WP

Temperature Range:

-32°C to +85°C (-25°F to +185°F)

Part No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Bend Radius Inches	Vacuum Inches Hg.	Weight lbs / ft	Standard Lengths
WA50-075	¾	1.22	150	3.0	29	0.48	100'
WA50-100	1	1.38	150	6.0	29	0.49	100'
WA50-125	1¼	1.72	150	6.0	29	0.75	100'
WA50-150	1½	1.89	150	6.5	29	0.80	100'
WA50-200	2	2.44	150	8.0	29	1.10	100'
WA50-250	2½	2.95	150	10.0	29	1.75	100'
WA50-300	3	3.46	150	12.0	29	2.24	100'
WA50-400	4	4.53	150	18.0	29	2.79	20'/100'
WA50-500	5	5.68	150	26.0	29	3.25	100'
WA50-600	6	6.54	150	31.0	29	5.75	20'/100'
WA50-800	8	8.82	150	42.0	29	6.59	20'/100'
WA50-1000	10	10.91	150	50.0	29	10.25	20'
WA50-1200	12	12.87	150	60.0	29	13.50	20'

*Call for additional fittings, lengths and assemblies.