




## WA65 Kanaline SR Flex-Line



### Application:

Heavy-duty, extra flexible suction and discharge hose for use in water service, dewatering, fish suction, general service, and rental/construction. **\*Hose is recommended for Suction Application ONLY**

### Construction:

**Tube** - Flexible PVC

**Reinforcement** - Synthetic yarn polyester braid

**Cover** - Flexible, orange PVC helix

### Temperature Range:

-25°C to +60°C (-13°F to +140°F)

### Pressure Loss Rate (% deduct from Catalog rate)

\*\* Temp rate means, hose temperature.  
Not atmosphere or material to transfer.

Working Pressure Loss	
104°F	-40%
122°F	-55%
140°F	-75%

Vacuum Pressure Loss	
104°F	-10%
113°F	-25%
122°F	-40%
140°F	-65%

Part No.	I.D. Inches	O.D. Inches	Max W.P. PSI @70°F	Bend Radius Inches @70°F	Vacuum Inches Hg. @70°F	Weight lbs / ft	Standard Lengths
WA65-150	1½	2.10	110	2.5	28.0	0.47	100'
WA65-200	2	2.60	100	4.0	28.0	0.70	100'
WA65-300	3	3.70	100	6.3	28.0	1.13	100'
WA65-400	4	4.78	75	7.1	28.0	1.74	100'
WA65-500	5	6.10	70	9.0	28.0	2.90	100'
WA65-600	6	7.17	70	10.2	28.0	3.88	100'
WA65-800	8	9.50	60	15.7	28.0	5.54	20'
WA65-1000	10	11.63	40	24.8	28.0	8.68	20'
WA65-1200	12	13.80	28	45.0	25.0	10.30	20'

## WA65 Kanaline SR Flex-Line Assemblies



Part No.	Hose Size & Length	End 1	End 2	Attaching Method
WA65-400BSIX020-B	4" x 20'	Ball - Type B	Socket - Type B	Crimp Sleeve
WA65-600BSIX010-B	6" x 10'	Ball - Type B	Socket - Type B	Crimp Sleeve
WA65-600BSIX020-B	6" x 20'	Ball - Type B	Socket - Type B	Crimp Sleeve
WA65-800BSIX010-B	8" x 10'	Ball - Type B	Socket - Type B	Crimp Sleeve
WA65-800BSIX020-B	8" x 20'	Ball - Type B	Socket - Type B	Crimp Sleeve
WA65-1000BSOX010-__*	10" x 10'	Ball - A or B	Socket - A or B	Crimp Sleeve
WA65-1000BSOX020-__*	10" x 20'	Ball - A or B	Socket - A or B	Crimp Sleeve
WA65-1200BSOX010-__*	12" x 10'	Ball - A or B	Socket - A or B	Crimp Sleeve
WA65-1200BSOX020-__*	12" x 20'	Ball - A or B	Socket - A or B	Crimp Sleeve

\*Specify (A)=Type A for Anfor Style or (B)=Type B for Bauer Style.



Part No.	Hose Size & Length	End 1	End 2	Attaching Method
WA65-200CESC020-AL	2" x 20'	Fem Cam Alum.	Male Cam Alum.	Spiral Bolt Clamp
WA65-300CESC020-AL	3" x 20'	Fem Cam Alum.	Male Cam Alum.	Spiral Bolt Clamp
WA65-400CESC020-AL	4" x 20'	Fem Cam Alum.	Male Cam Alum.	Spiral Bolt Clamp
WA65-600CESC010-AL	6" x 10'	Fem Cam Alum.	Male Cam Alum.	Spiral Bolt Clamp
WA65-600CESC020-AL	6" x 20'	Fem Cam Alum.	Male Cam Alum.	Spiral Bolt Clamp
WA65-800CESC010-AL-__*	8" x 10'	Fem Cam Alum. - 1 or 2	Male Cam Alum. - 1 or 2	Spiral Bolt Clamp
WA65-800CESC020-AL-__*	8" x 20'	Fem Cam Alum. - 1 or 2	Male Cam Alum. - 1 or 2	Spiral Bolt Clamp

\*Specify (N)=Type 1 for NECO Style or (P)=Type 2 for PT Style. See Page 174 for Detailed Type Explanation.

\*Call for additional fittings, lengths and assemblies.