



NOTE: CA FAN HEADS REPLACE CFH FAN HEADS

CA - INDUSTRIAL GRADE CIRCULATING FANS

Canarm LFI's CA circulating fans economically provide relief from summer heat by creating a gentle air movement. They effectively cool large areas in factories, stores, restaurants and other public places. These fans have a low RPM motor which allows them to operate quietly.

The Floor Pedestal type fans come with a sturdy base and are supported by an adjustable tubular steel post which provides maximum stability. The Wall Mount fans are anchored with a sturdy wall bracket. There is also an optional ceiling mount.

On all fan models, the fan assembly can be tilted on a swivel bracket to direct air stream upwards or downwards. Available with oscillating motor on the pedestal and wall models.

FEATURES

- Rugged, high performance model.
- · Available in 24" & 30" sizes.
- 1/4 HP, 3 speed, totally enclosed ball bearing motor with thermal overload protection.
- Fan motor RPM 1100/950/850.
- · Available with oscillating motor on the pedestal and wall models.
- · Heavy gauge aluminum, well balanced fan blades.
- · Air stream adjustable in all directions.
- · Complete with 10', 120V grounded cord set.
- Attractive powder coated front and rear guards, meet OSHA standards.



PERFORMANCE SPECIFICATIONS

| MODEL NUMBER | FAN SIZE | DESCRIPTION | СҒМ | VOLT | AMPS | SHIPPING WEIGHT (LBS) |
|-----------------|-------------|---------------------|----------------|------|------|--------------------------|
| HEADS ONLY | | | | | | |
| CA24-C | 24" | 3 SPEED | 7100/6300/5300 | 115 | 2.7 | 40 |
| CA24OSC-C | | 3 SPEED OSCILLATING | 7100/6300/5300 | 115 | 2.7 | 40 |
| CA30-C | 30" | 3 SPEED | 8300/7300/6300 | 115 | 2.7 | 50 |
| CA30OSC-C | | 3 SPEED OSCILLATING | 8300/7300/6300 | 115 | 2.7 | 50 |

OUICK REFERENCE

Use this table to make sure you order the correct fan replacement parts.


FAN HEAD MOUNTING ACCESSORIES SHOWN BELOW.


| OLD MODEL | REPLACED WITH | | | | |
|---------------------------------|-------------------|--|--|--|--|
| PEDESTAL FANS - OSCILLATING | | | | | |
| CA24POSC-C | CA24OSC-C + CFKPB | | | | |
| CA30POSC-C | CA30OSC-C + CFKPB | | | | |
| PEDESTAL FANS - NON OSCILLATING | | | | | |
| CA24P-C | CA24-C + CFKPB | | | | |
| CA30P-C | CA30-C + CFKPB | | | | |


| OLD MODEL | REPLACED WITH | | | | |
|-----------------------------|------------------|--|--|--|--|
| WALL FANS - OSCILLATING | | | | | |
| CA24WOSC-C | CA24OSC-C + CFWB | | | | |
| CA30WOSC-C | CA30OSC-C + CFWB | | | | |
| WALL FANS - NON OSCILLATING | | | | | |
| CA24W-C | CA24-C + CFWB | | | | |
| CA30W-C | CA30-C + CFWB | | | | |

VELOCITY MAPPING CHARTS

These charts indicate the air distribution patterns of the CA fans. They are a graphic illustration of air velocity in feet per minute.









MOUNTING ACCESSORIES

| MODEL | DESCRIPTION | WEIGHT (LBS) |
|-------|---|-----------------|
| CFKPB | KNOCK DOWN PEDESTAL BASE | 36 |
| CFWB | WALL BRACKET | 6 |
| CFCM | CEILING MOUNT (NON OSCILLATING FANS ONLY) | 9 |