

5-5/8" Totally Enclosed Fan/Blower Motors

Unit Heater Fan Motors

Features:


- Continuous Duty, Air Over
- Permanent Split Capacitor
- Sleeve & Ball Bearing
- Thermally Protected
- 60 Hz
- 48Y Frame



HP	RPM	Speeds	Volts	Amps	Stock		Rotation	Capacitor	Encl.	Base	Dim.		Notes
					Number	Bearings					Ref.		
1/3	1075	1	115	5.3	US1036	Sleeve	REV.	Included	TE	Resilient	3		31,89,279
1/3	1075	1	115	5.3	US1036NB	Sleeve	REV.	Included	TE	None	7		31,279
1/3	1075	1	115	5.3	UHH1036	Ball	REV.	Included	TE	Resilient	3		31,89,279
1/3	1075	1	115	5.3	UHH1036V1	Ball	REV.	Included	TE	Resilient	9		31,89,279
1/3	1140	1	115/208-230	3.3/1.7	732A	Ball	REV.	Included	TE	Resilient	4		29,189
1/3	1075	1	208-230	2.2	UHH1036	Ball	REV.	Included	TE	Resilient	9		6,31
1/3	1100	2	230	1.7-1.1	UHH1036NB	Ball	REV.	Included	TE	None	8		9,31,360
1/3	1100	2	115	4.3-1.8	UHH1036NB	Ball	REV.	Included	TE	None	8		9,31,360
1/3	1725	1	115/230	2.9/1.5	768A	Ball	REV.	Included	TE	Resilient	1		29,189
1/2	1140	1	115/208-230	5.6/2.8	733A	Ball	REV.	Included	TE	Resilient	5		29
1/2	1725	1	115/230	5.4/2.7	769A	Ball	REV.	Included	TE	Resilient	6		29

Notes:

- 6. 60/50 HZ
- 9. Reversing plug
- 29. 60°C Ambient
- 31. 40°C Ambient
- 89. 60" leads
- 189. Includes split bushing and key for 5/8" shafts
- 279. 4 thru bolts and 4 dummy studs on a 5.15 dia. bolt circle
- 360. 4 thru bolts in a 5.15 dia. bolt circle



Approximate Dimensions

Ref.	BM	R	C	N	T	D
1	6.75		11.83	5.08	0.88	3.00
2	4.25		9.80	5.55	1.52	3.00
3	4.61		7.60	2.99	0.65	3.50
4	6.50		11.58	5.08	0.88	3.00
5	7.25		12.28	5.03	0.88	3.00
6	7.50		12.58	5.08	0.88	3.00
7	4.61		7.60	2.99	0.65	
8	5.11	5.67	10.61	5.50	2.56	
9	4.61	5.17	10.11	5.50	0.65	3.50