

# Three Phase ODP Resilient Base Motors

## Pumps - Blowers - Conveyors - Industrial Duty

### Features:

- Ball Bearing
- Class A and B Insulation
- Continuous Duty
- Open Dripproof
- 40°C Ambient
- 60 HZ
- 1/4 thru 5 HP



BK3054



H850

HP	RPM	Volts	Full Load Amps	Service Factor	Frame	Stock Number	Protector	Insul. Class	Approx. "C"	Dim "AG"	Notes	
1/3	1725	200-230/460	1.1-1.3/6	1.35	48	H264	None	B	9.4	7.0	1,6	
		200-230/460	1.1-1.2/6	1.00	48Y	H264A	None	B	9.6	8.0	6 <b>New!</b>	
		200-230/460	1.4-1.6/8	1.35	56	H262V1	None	B	9.8	7.9		
1/2	3450	460/200-230	1.0/1.9-2.0	1.60	56	H840	Auto	B	12.2	10.3	35,82	
		208-230/460	2.0/1.0	1.25	56	BK3054V1	Auto	B	11.4	9.5	26	
	1725	460/200-230	1.1/1.8-2.2	1.25	56	H275V1	None	B	9.8	7.9	26	
		460/200-230	1.5/2.5-3.0	1.25	56	H850	Auto	B	12.2	10.3	35,82	
		575	.70	1.25	56	H940	Auto	B	11.1	9.1		
575	.88	1.25	56	H957	None	A	9.8	7.9				
3/4	3450	200-230/460	2.6-2.4/1.2	1.50	56	H449	None	B	11.1	9.1		
		460/200-230	1.4/2.8-2.8	1.50	56	H841V1	Auto	B	12.7	10.8	26,35,82	
		575	1.05	1.50	56	5BK3072	Auto	A	11.4	9.5		
	1725	208-230/460	2.5/1.25	1.25	56H	BK3074	Auto	B	11.9	10.0		
		460/200-230	1.7/2.9-3.4	1.25	56	H851V1	Auto	B	12.2	10.3	26	
		575	.90	1.25	56	H941	Auto	B	11.1	9.1		
		575	1.0	1.25	56	H958	None	A	10.1	8.1		
	1	3450	200-230/460	3.2-3.0/1.5	1.40	56	H464	None	B	11.1	9.1	
			230/460	3.1/1.55	1.40	56H	BK3102	Auto	A	11.9	10.0	
			460/200-230	1.8/3.5-3.6	1.40	56H	H842V1	Auto	B	12.9	11.0	26,35,82
575			1.5	1.40	56H	H950	Auto	B	12.7	10.8	82	
1725		575	1.6	1.40	56H	5BK3102	Auto	B	11.9	10.0	1	
		200-230/460	3.3-3.4/1.7	1.30	56	H1031	None	B	11.5	9.5	26, 118	
		200-230/460	3.4-3.4/1.7	1.25	56	H615V1	None	B	11.1	9.1	26	
		208-230/460	3.6/1.8	1.25	56H	RB3104A	Auto	B	11.8	9.8		
		460/200-230	1.9/3.5-3.8	1.15	56H	H852	Auto	B	12.7	10.8	35,82	
		460/200-230	1.9/3.5-3.8	1.15	56HZ	H888	Auto	B	12.6	10.3	1,15,35,82	
		575	1.4	1.25	56	H959	None	B	11.1	9.1		
		575	1.5	1.15	56H	H942	Auto	B	12.7	10.8	82	

### Notes:

- Item to be discontinued when stock is depleted
  - 60/50 Hz
  - 56HZ = 7/8" key x 2-5/16" shaft
  26. Extended thru bolts, shaft end only
  35. Quick Connect design bracket
  82. Horizontal mount only
  118. TEAO
  274. 48Z = 1/2 flat X 1.88 shaft, with 48 FR base
- See page 272 for mounting dimensions

### Shaft Dimensions

- 56 = 5/8" Keyed x 1-7/8"
- 56H = 5/8" Keyed x 1-7/8"

