

CPTH-12 Heat Pump

Optional

Ion Generation

Total Positive/Negative Ion Output >350M ions/cc/sec

Optional HEPA Kit

HEPA Certified 99.97% @0.3 micron Filtration

Cooling Capacity

Btu/hr 11,500
Operating Range: Min-Max F° 65°-95°

Heating Capacity

Btu/hr 10,300
Operating Range: Min-Max F° 40°-80°

Dimensions

Width (Inches) 19
Depth (Inches) 26.5
Height (Inches) 41.7
Weight (Pounds) 165

Electrical

Specifications

Power Supply (Volts) 115
Current Consumption (Amps) 11.5
Fuse Size (Amps) 15
Plug Configuration 5-15
Voltage (Min-Max) 105-125
Power Cord Length (Feet) 8

Fan

Characteristics

Evaporator:
Air Flow (CFM) High/Low 400/355
Condenser:
Air Flow (CFM) High/Low 1005/888

Compressor

Specifications

Compressor Type Rotary
Refrigerant Type R-410A

Safety Devices

Compressor Overcurrent Protection Yes
Fan Motor Protection Yes
Anti-Freeze Thermostat Yes
Fan Mode Switch Yes
Automatic Restart Yes
Automatic Tank Shut Off Yes
Audible Condensate Shut Off Alarm Yes
Built In Safety Switch for Condensate Pump Yes
Condensate Tank Capacity (Gal) 4.9
LED Control Panel with Timer Yes
UL2998 Certified Ozone Free Yes



ClimaTemp

Portables

www.Clima-Temp.com
1-844-349-5665