

KAKA-020E-TAC

HCFC, R-22, 60 Hz, 3 -phase, 208/230 V

Low Temperature



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	-25 / 105	-40 / 105
RG(°F)/Liq(°F)	65.0 / 105.0	65.0 / 105.0
Capacity (Btu/hr)	3920	2180
Power (Watts):	952	730
Current (Amps):	4.60	4.30
EER (Btu/Wh):	4.10	3.00
Mass Flow (lbs/hr):	52	29
<u>Sound Data</u>		
Sound Power (dBA):		
Vibration (mils(peak-peak)):		4.76 Max
Record Date:	2007-01-03	

Mechanical

Number of Cylinders:	2	Displ(in ³ /Rev):	4.20
Bore Size(in):	1.69	Displ(ft ³ /hr):	255.09
Stroke(in):	0.94		
Overall Length (in):	14.38	Mounting Length (in):	8.19
Overall Width (in):	9.50	Mounting Width (in):	6.38
Overall Height (in):	10.44	Mounting Height (in):	11.19 *
Suction Size (in):		7/8 Sweat	
Discharge Size (in):		1/2 Flare	
Oil Recharge (oz):		20	
Initial Oil Charge (oz):		22	
Net Weight (lbs):		101	
Internal Free Volume (in ³):			
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	50.0	MCC (Amps):	9.5	UL File No:	SA-2337
LRA-Half Winding:		RPM:	1750	UL File Date:	23-Jul-1984
LRA Low*:		Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):		6.8			
RLA(=MCC/1.56;use for breaker & wire size)		6.1			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-404A HFC	50	3	200/220	Medium Temperature
R-404A HFC	60	3	208/230	Medium Temperature
R-22 HCFC	50	3	200/220	High Temp
R-22 HCFC	50	3	200/220	Medium Temperature
R-22 HCFC	50	3	200/220	Low Temperature
R-22 HCFC	60	3	208/230	High Temp
R-22 HCFC	60	3	208/230	Medium Temperature
R-502 CFC	50	3	200/220	UL Medium Temp
R-502 CFC	60	3	208/230	UL Medium Temp
R-407C HFC	50	3	200/220	Medium Temperature

Alternate Applications

<u>Refrigerant</u>	<u>Freq (Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
R-407C HFC	50	3	200/220	Low Temperature
R-407C HFC	60	3	208/230	Medium Temperature
R-407C HFC	60	3	208/230	Low Temperature
R-407A HFC	50	3	200/220	Medium Temperature
R-407A HFC	50	3	200/220	Low Temperature
R-407A HFC	60	3	208/230	Medium Temperature
R-407A HFC	60	3	208/230	Low Temperature