

ZF13K4E-TF5

HFC, R-404A, 60 Hz, 3 -Phase, 200/230 V

Low Temp, Liquid Injected

COPELAND™

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	-25	-40
Condensing Temp. (°F)	105	105
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	105	105
Capacity (Btu/hr)	13000	8750
Power (W):	2850	2730
Current (Amps):	8.95	8.65
EER (Btu/Wh):	4.55	3.20
Mass Flow (lbs/hr):	238	163
Sound Data -25 / 105		
Sound Power (dBA):	78 Avg	83 Max
Vibration mils(peak-peak):	2.0 Avg	3.0 Max
Record Date:	2018-05-03	

Electrical

LRA-High*(Amp):	99.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	18.5
Max Operating Current(Amp):	16.0
RLA, MCC/1.4;use for contactor selection (Amp):	13.2
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	11.9
RPM:	3500
Box IP	21
UL File No:	SA-2337
UL File Date:	1994-06-15
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.	

Mechanical

Displacment	4.10
Displacment(ft^3/hr):	497.78
Overall Length (in):	9.67
Overall Width (in):	10.12
Overall Height (in):	17.40
Mounting Length (in):	7.50
Mounting Width (in):	7.50
Mounting Height (in):	18.15 *
Suction Size (in),Type:	7/8 Stub
Discharge Size (in),Type:	1/2 Stub
Initial Oil Charge (oz):	64
Oil Recharge (oz):	60
Net Weight (lbs):	85.0
Internal Free Volume (in^3):	367.2
Horse Power:	4.00
*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Capacitors

Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-134a HFC	200/230	3	60	High Temp
R-134a HFC	200/220	3	50	High Temp
R-404A HFC	200/230	3	60	Low Temp, Low Condensing
R-448A HFO	200/230	3	60	Low Temp, Low Condensing
R-449A HFO	200/230	3	60	Low Temp, Low Condensing
R-404A HFC	200/220	3	50	Low Temp, Low Condensing
R-448A HFO	200/220	3	50	Low Temp, Low Condensing
R-449A HFO	200/220	3	50	Low Temp, Low Condensing

Alternate Applications

<u>Refrigerant</u>	<u>Voltage</u>	<u>Phase</u>	<u>Freq (Hz)</u>	<u>Application</u>
R-507 HFC	200/230	3	60	Low Temp, Low Condensing
R-134a HFC	200/230	3	60	Low Temp, Liquid Injected
R-449A HFO	200/220	3	50	Low Temp, Liquid Injected
R-22 HCFC	200/230	3	60	Low Temp, Liquid Injected
R-507 HFC	200/230	3	60	Low Temp, Liquid Injected
R-404A HFC	200/220	3	50	Low Temp, Liquid Injected
R-407C HFC	200/230	3	60	Low Temp, Liquid Injected
R-407A HFC	200/230	3	60	Low Temp, Liquid Injected
R-407F HFC	200/230	3	60	Low Temp, Liquid Injected
R-407F HFC	200/220	3	50	Low Temp, Liquid Injected
R-448A HFO	200/230	3	60	Low Temp, Liquid Injected
R-448A HFO	200/220	3	50	Low Temp, Liquid Injected
R-407A HFC	200/220	3	50	Low Temp, Liquid Injected
R-449A HFO	200/230	3	60	Low Temp, Liquid Injected
R-507 HFC	200/220	3	50	Low Temp, Liquid Injected
R-134a HFC	200/220	3	50	Low Temp, Liquid Injected
R-22 HCFC	200/220	3	50	Low Temp, Liquid Injected
R-134a HFC	200/220	3	50	Medium Temp, Liquid Injected
R-22 HCFC	200/220	3	50	Medium Temp, Liquid Injected
R-134a HFC	200/230	3	60	Medium Temp, Liquid Injected
R-404A HFC	200/220	3	50	Medium Temp, Liquid Injected
R-507 HFC	200/230	3	60	Medium Temp, Liquid Injected
R-404A HFC	200/230	3	60	Medium Temp, Liquid Injected
R-448A HFO	200/230	3	60	Medium Temp, Liquid Injected
R-448A HFO	200/220	3	50	Medium Temp, Liquid Injected
R-507 HFC	200/220	3	50	Medium Temp, Liquid Injected
R-22 HCFC	200/230	3	60	Medium Temp, Liquid Injected
R-449A HFO	200/230	3	60	Medium Temp, Liquid Injected
R-449A HFO	200/220	3	50	Medium Temp, Liquid Injected
R-407C HFC	200/220	3	50	UL Low Temp
R-407A HFC	200/220	3	50	UL Low Temp