

ZR21K5E-PFJ

HFC, R-407C, 60Hz, 1- Phase, 265 V
Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	50 / 100
RG(°F)/Liq(°F)	65.0 / 115.0	70.0 / 85.0
Capacity (Btu/hr)	20200	27200
Power (Watts):	2060	1385
Current (Amps):	7.75	5.50
EER (Btu/Wh):	9.80	19.70
Mass Flow (lbs/hr):	294	336
Sound Power (dBA):	68 Avg	73 Max
Vibration (mils(peak- Record Date:	2.0 Avg 2011-01-05	3.0 Max

Mechanical

Number of Cylinders:	0	Displ(in ³ /Rev):	1.77
Bore Size(in):	0.00	Displ(ft ³ /hr):	214.86
Stroke(in):	0.00		
Overall Length (in):	9.50	Mounting Length (in):	7.50
Overall Width (in):	9.50	Mounting Width (in):	7.50
Overall Height (in):	15.86	Mounting Height (in):	16.08 *
Suction Size (in):		3/4 Stub	
Discharge Size (in):		1/2 Stub	
Oil Recharge (oz):		19	
Initial Oil Charge (oz):		25	
Net Weight (lbs):		47.2	
Internal Free Volume (in ³):		131.0	
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	54.0	MCC (Amps):	14.5	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	
LRA Low*:		Max Operating Current:	11.0		
RLA(=MCC/1.4;use for contactor selection):		10.4			
RLA(=MCC/1.56;use for breaker & wire size		9.3			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					
Type	Part No	Low MFD	High MFD	Volts	User Description
Start Capacitor	014-0061-27	88.0	106.0	330	OPTIONAL
Run Capacitor	014-0064-07	35.0	0.0	370	

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-407C HFC	50	1	220/240	Air Conditioning
R-22 HCFC	50	1	220/240	Air Conditioning
R-22 HCFC	60	1	265	Air Conditioning