

ZS13KAE-PFV

HFC, R-134a, 60Hz, 1- Phase, 208/230 V

High Temp



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	20 / 120
RG(°F)/Liq(°F)	65.0 / 130.0	65.0 / 120.0
Capacity (Btu/hr)	13200	8250
Power (Watts):	1400	1160
Current (Amps):	6.20	5.10
EER (Btu/Wh):	9.40	7.10
Mass Flow (lbs/hr):	229	131
Sound Power (dBA):	72 Avg	77 Max
Vibration (mils(peak-peak)):	2.0 Avg	3.0 Max
Record Date:	2012-03-17	

Mechanical

Number of Cylinders:	0	Displ(in^3/Rev):	1.77
Bore Size(in):	0.00	Displ(ft^3/hr):	214.86
Stroke(in):	0.00		
Overall Length (in):	9.69	Mounting Length (in):	7.50
Overall Width (in):	9.69	Mounting Width (in):	7.50
Overall Height (in):	15.72	Mounting Height (in):	16.00 *
Suction Size (in):	3/4 Stub		
Discharge Size (in):	1/2 Stub		
Oil Recharge (oz):	19		
Initial Oil Charge (oz):	25		
Net Weight (lbs):	46.9		
Internal Free Volume (in^3):	131.0		
Horse Power:	1.8		
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	56.0	MCC (Amps):	16.8	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	16-Dec-2003
LRA Low*:		Max Operating Current:	12.5		
RLA(=MCC/1.4;use for contactor selection):	12				
RLA(=MCC/1.56;use for breaker & wire size selection):	10.8				
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					
Type	Part No	Low MFD	High MFD	Volts	User Description
Start Capacitor	014-0061-27	88.0	106.0	330	OPTIONAL
Run Capacitor	014-0064-07	35.0	0.0	370	

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-22 HCFC	60	1	208/230	High Temp
R-404A HFC	60	1	208/230	Medium Temperature
R-507 HFC	60	1	208/230	Extended Medium Temp
R-407C HFC	60	1	208/230	High Temp
R-407A HFC	60	1	208/230	Extended Medium Temp
R-404A HFC	60	1	208/230	Extended Medium Temp
R-507 HFC	60	1	208/230	Medium Temperature

ZS13KAE-PFV

HFC, R-134a, 60Hz, 1- Phase, 208/230 V
High Temp



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Service Parts

<u>Reference</u>	<u>Component</u>	<u>Quantity</u>	<u>Description</u>	<u>Comment</u>
99	527-0044-15	1	SPACER-MOUNTING ASSM	
99	529-0060-24	1	POWER CABLE-MOLDED PLUG	
99	914-0036-03	1	CAP START KIT	
99	914-0037-11	1	RUN CAP KIT W/CLAMP	
99	918-0052-00	1	CRANKCASE HEATER KIT	240V 40W WRAP AROUND
99	918-0052-01	1	CRANKCASE HEATER KIT	120V 40W WRAP AROUND
99	940-0001-79	1	RELAY-POTENTIAL KIT	
99	998-0358-00	1	HEATER JUNCTION BOX KIT	
99	998-0510-38	1	SERV VALVE KIT 3/4 SWT	SUCTION
99	998-0510-44	1	SERV VALVE KIT 1/2 SWT	DISCHARGE ROTALOCK

ZS13KAE-PFV

HFC, R-134a, 60Hz, 1- Phase, 208/230 V

High Temp

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Accessories

<u>Category</u>	<u>PartNumber</u>	<u>Description</u>
Crankcase Heaters	018-0094-00	Crankcase Heater, 240V, 40W
	018-0094-01	Crankcase Heater, 120V, 40W
	018-0094-03	Crankcase Heater, 480V, 40W, 21.25" Lead Length
	018-0094-04	Crankcase Heater, 575V, 40W, 21.25" Lead Length
	918-0052-00	Crankcase Heater Kit, 240V, 40W, Wrap Around, 21" Lead Length
	918-0052-01	Crankcase Heater Kit, 120V, 40W, Wrap Around, 21" Lead Length
	998-0358-00	Crankcase Heater Enclosure Box
Discharge Line	998-0540-02	Discharge Line Thermostat Kit, 1/2" DLT-Stat 36" Leads, 2-Wire
	998-0548-00	Discharge Line Thermostat Kit, 1/2" DLT-Stat 36" Leads With Alarm
	998-7022-02	Discharge Line Thermostat Kit, 1/2", 36" Leads (Conduit Ready)
Molded Plugs	529-0060-04	Molded Plug Kit, 10 GA Wire, 42" Length, Black / Yellow / Red
	529-0060-24	Molded Plug Kit, 10 GA Wire, 42" Length, Black / Charcoal Gray / Light Gray
	529-0106-00	Transport Style Molded Plug With Retention Clip Kit - 12 GA Wire
	998-0230-00	Conduit Adapter Kit, for molded plug. Includes adapter, retaining clip, 29" conduit. Molded Plug not included.
Mounting	527-0044-15	Spacer Mounting Kit, 30-35 Durometer, 1.45" OD, 0.44" ID, 0.75" Height
Service Valves and	998-0034-01	Stub Tube to Rotalock, 3/4" Sweat to 1 1/4"-12 Thread
	998-0034-15	Stub Tube to Rotalock, 1/2" Sweat (OD Applied) to 1"-14 Thread
	998-0069-01	Stub Tube to Rotalock, 3/4" Sweat to 1 1/4"-12 Thread and 1/2" Sweat to 1"-14 Thread
	998-0510-98	Service Valve Kit, 1"-14 Thread to 1/2" Sweat
	998-0511-02	Service Valve Kit, 1 1/4"-12 Thread to 3/4" Sweat
	998-5100-42	Service Valve Kit, 1 1/4"-12 Thread to 3/4" Sweat and 1"-14 Thread to 1/2" Sweat
	998-5100-48	Service Valve Kit, 1 1/4"-12 Thread to 7/8" Sweat and 1"-14 Thread to

<u>Category</u>	<u>PartNumber</u>	<u>Description</u>
		1/2" Sweat

Common U.S. Service Bill Of Materials

	Suction Connection	Suction Size	Discharge Connection	Discharge Size	Electrical Connection	Mounting Assembly	Sight Glass	Crankcase Heater	Schraeder Valve	Tandem Ready	Module Voltage
818	Stub	3/4"	Stub	1/2"		Yes	-	-	-	-	-

* Note: For all other Bill Of Material descriptions (Including International and Customer Specific Bills of Materials) contact your sales representative or the Application Engineering Department.