



ZERO LOSS COMPRESSED AIR CONDENSATE TRAP

POWERS THROUGH CONDENSATE BUILDUP. Ideal for compressor applications up to 100 hp (500 SCFM). The WaterHog™ design avoids small passages common on competitor designs, ensuring clog-free operation.

FULLY AUTOMATIC OPERATION. No timer or manual settings.

NO ELECTRICAL CONNECTIONS. WaterHog™ is powered by compressed air, avoiding the need for electrical wiring and connections.

ENERGY SAVING OPERATION. Zero compressed air loss*. Check with your utility to see if it qualifies for energy efficiency incentives. WaterHog™ pays for itself when replacing open condensate drain valves or timer traps.

LOW PROFILE. The 4.7" vertical operating height allows WaterHog™ to fit where other larger units can't.

CONTROL DEVICES, LLC
1555 LARKIN WILLIAMS ROAD
FENTON, MISSOURI 63026
+1 636.660.7100
+1 800.233.1477
FAX +1 314.781.7859
WWW.CDIVALVE.COM

*When properly installed with balance line.



- Max Operating Pressure (PSIG): 200
- Min/Max Control Pressure (PSIG): 40/130
- Min/Max Temperature (F): + 34/170
- Inlet/Outlet Connections (npt): ½"
- Packaged Weight (lbs): 13

