









One-On-One™ Direct Replacement Motors

	MARS NO.	MFG. NO	HP	VOLTS	RPM/SPEEDS	ROT	AMPS	DIMENSIONS		
								A	B	C
Prestcold (con't)										
	05821	5KSM81HFL3006T	16W	230	1550/1	CW OSE	.55	.5	3.5	-
	3 1/2 inch diam., enclosed 3 tapped holes or side pad, shaded pole, 1/4 inch threaded shaft									
	Replaces: Prestcold No, 401-0033-01									
Revco										
	90964	301-6374	-	110/120	2400	CW OSE	.30/.27	.75	.33	1.0
	C-Frame ball bearing evaporator fan motor with mounting bracket and wiring harness, .1815 shaft dia.									
	Replaces: Revco 33230H01									
	90967	301-6472	1/70	115	3000	CW OSE	.80	1.00	.88	-
	C-Frame ball bearing motor, .1875 shaft dia.; with machined shaft									
	Replaces:									
	90969	903-2329	18W	115	3000	CCW OSE	.25	-	.65	-
	Fan tubaxial motor resilient thrust washer construction									
	Replaces: Revco 88789H01									
Reznor										
	D461	-	1/8	480	3200/1	CCW SE	.32	3.33	4.25	-
	PSC, sleeve bearing, 5/16 inch dia. shaft									
	Replaces: 7162-0396									
Rheem										
	03149	5KCP39FGT318S	1/3	460	1075/1	REV	0.9	3.75	4.48	-
	5 1/2 inch diam., totally enclosed, sleeve bearing, 5 MFD @ 370V capacitor required (MARS No. 12005), thru bolt or shell mount									
	Replaces: Rheem 51-23063-11									

ONE-ON-ONE

