

TF1 TOTAL FILTER FLUSHING ADAPTER

- Easy flushing with connection via the Fernox Total Filter TF1
- Provides full flow rate to optimise cleaning efficiency
- Fernox TF1 Flushing Adapter is rated to 85°C and fully acid resistant



Product Uses

The Fernox TF1 Flushing Adapter is designed for easy connection of your Fernox Powerflow Flushing Machine to the heating system via a Fernox TF1 Total Filter. The Fernox TF1 Flushing Adapter fits on the same fixings and valves as either a 22 mm or 28 mm Fernox TF1 Total Filter.

Instructions for use

1. Close the isolating valves on the Fernox Total Filter TF1 and remove from system leaving the valves in situ.
2. Using either the original rubber seals or replacements provided with the Fernox TF1 Flushing Adapter, fit in place of the filter as show in the photograph.
3. Connect your Powerflow Flushing Machine to the Fernox TF1 Flushing Adapter. Use only PLASTIC (PP) $\frac{3}{4}$ " female nut liner and seals, as provided with the Fernox Powerflow Flushing Machine and Fernox TF1 Flushing Adapter. Secure these to the hoses with screw clamps.

Care and Maintenance

Used appropriately the Fernox TF1 Flushing Adapter is maintenance free. The unit is factory sealed and should not be disassembled. Spares parts for the Fernox TF1 Flushing Adapter are available from our sales office by calling 0330 100 7750.