

INDIRECT FIRED HEATERS



Indirect fired heat exchangers allow external exhaust of combustion products. This series contains heavy-duty flat free tires and a slim design for easy site mobility and transportation. Oil, diesel, propane, and natural gas options are available. All units contain a digital voltage display and have the capability to be thermostatically controlled.



FVO-200RC



FVO-200RC42



FVNP-200RC

MODEL	FVO-200RC	FVO-200RC42	FVNP-200RC
FUEL TYPE	OIL	OIL	DUAL FUEL - LP/NG
BTU/HR	185,000	185,000	200,000
CFM	2,600 (DUCT UP TO 150')	2,600 (DUCT UP TO 150')	2,600 (DUCT UP TO 150')
POWER REQUIREMENTS	115V/15A	115V/15A	115V/15A
FUEL TANK CAPACITY* RUN TIME* FUEL CONSUMPTION*	23 US GAL TANK 21 HR RUN TIME	42 US GAL TANK 38 HR RUN TIME	EXTERNAL
HEAT EXCHANGER	16 GAUGE 304 SS	16 GAUGE 304 SS	16 GAUGE 304 SS
AIR OUTLET DIA. AIR INLET DIA.	(1) 12" or (1) x 16" (1) X 12"	(1) 12" or (1) x 16" (1) X 12"	(1) 12" or (1) x 16" (1) X 12"
BURNER TECHNOLOGY	RIELLO BURNER	RIELLO BURNER	RIELLO BURNER
RETURN AIR	YES	YES	YES
L x W x H	51.5" x 27" x 48"	51.5" x 27" x 48"	51.5" x 27" x 44"
WEIGHT	350 LBS	425 LBS	300 LBS