

DU180H

CFM	Static Pressure in Inches W.G.														
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000	3.250	3.500
	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP
1000			639 5.2 / 0.18	774 8.2 / 0.30	893 10.2 / 0.42	998 11.6 / 0.56	1094 13.0 / 0.71	1181 14.9 / 0.85	1263 16.4 / 1.01	1337 17.8 / 1.17	1408 19.2 / 1.34	1477 21 / 1.52	1541 22 / 1.70	1600 23 / 1.88	1661 24 / 2.08
1500			694 6.5 / 0.26	806 8.7 / 0.39	909 10.5 / 0.54	1006 11.7 / 0.70	1096 13.0 / 0.87	1182 14.9 / 1.05	1263 16.4 / 1.24	1339 17.9 / 1.43	1411 19.3 / 1.63	1481 21 / 1.84	1546 22 / 2.05	1609 23 / 2.27	1670 24 / 2.49
2000		683 7.3 / 0.25	784 9.2 / 0.38	876 10.2 / 0.53	964 11.4 / 0.69	1047 12.1 / 0.87	1127 13.8 / 1.06	1203 15.3 / 1.26	1278 16.7 / 1.47	1349 18.0 / 1.68	1417 19.4 / 1.91	1484 21 / 2.14	1548 22 / 2.38	1610 23 / 2.63	1671 24 / 2.88
2500	700 8.7 / 0.25	803 10.7 / 0.40	891 11.7 / 0.55	970 12.7 / 0.72	1046 12.1 / 0.90	1118 13.6 / 1.09	1188 15.0 / 1.30	1255 16.3 / 1.51	1321 17.5 / 1.74	1385 18.7 / 1.97	1448 20 / 2.22	1509 21 / 2.47	1567 22 / 2.73	1625 23 / 2.99	
3000	839 12.3 / 0.43	928 13.6 / 0.61	1006 13.9 / 0.79	1077 14.2 / 0.98	1144 15.8 / 1.18	1208 17.2 / 1.39	1270 17.8 / 1.61	1330 18.6 / 1.84	1388 19.4 / 2.08	1446 20 / 2.33	1502 21 / 2.59	1557 22 / 2.86			
3500	979 14.8 / 0.68	1057 15.8 / 0.89	1127 16.6 / 1.10	1191 18.4 / 1.31	1252 19.3 / 1.54	1309 20 / 1.77	1366 21 / 2.01	1420 21 / 2.26	1472 22 / 2.51	1524 23 / 2.78					
4000	1119 17.4 / 1.02	1188 19.3 / 1.25	1251 21 / 1.49	1310 22 / 1.73	1366 22 / 1.98	1419 23 / 2.24	1470 24 / 2.50	1520 24 / 2.77							
4500	1259 22 / 1.45	1321 23 / 1.71	1379 24 / 1.98	1433 25 / 2.25	1484 26 / 2.52	1533 26 / 2.80									
5000	1399 26 / 1.99	1455 27 / 2.28	1508 27 / 2.58	1558 28 / 2.88											
5500	1539 30 / 2.64	1590 30 / 2.97			1539 27 / 2.64										

Max Sizeable RPM = 1800 RPM. Table shown extended beyond this point for reference only.

- Motor 00112ET3H145T-W22 has an rpm range of 600 to 1150.
- Motor 00112OT3H145T-S has an rpm range of 600 to 1150.
- Motor 00152ET3E182T-W22 has an rpm range of 600 to 1150.
- Motor 00152ET3H182T-W22 has an rpm range of 600 to 1150.
- Motor 00152OT3E182T-S has an rpm range of 600 to 1150.
- Motor 00158ET3H145T-W22 has an rpm range of 600 to 1750.
- Motor 00212ET3E184T-W22 has an rpm range of 600 to 1150.
- Motor 00212ET3H184T-W22 has an rpm range of 600 to 1150.
- Motor 00218ET3H145T-W22 has an rpm range of 600 to 1750.
- Motor 00218OT3E56Z-S48PP has an rpm range of 600 to 1700.
- Motor 00318ET3H182T-W22 has an rpm range of 600 to 1750.
- Motor BMN145-2.0I2-CS-UB1-50 (1200RPM) has an rpm range of 600 to 1200.
- Motor BMN145-2.0I2-CS-UB1-60 (1200RPM) has an rpm range of 600 to 1200.
- Motor BMN145-2.0I2-ES-UB1-50 (1800RPM) has an rpm range of 600 to 1800.
- Motor BMN145-2.0I2-ES-UB1-60 (1800RPM) has an rpm range of 600 to 1800.
- Motor DHP0026 has an rpm range of 600 to 1150.
- Motor DHP0034 has an rpm range of 600 to 1750.
- Motor DTP0014 has an rpm range of 600 to 1750.
- Motor DTP0016 has an rpm range of 600 to 1150.
- Motor DTP0024 has an rpm range of 600 to 1740.
- Motor DTP0026 has an rpm range of 600 to 1150.
- Motor DTP0034 has an rpm range of 600 to 1755.
- Motor DTP0034-50HZ has an rpm range of 600 to 1438.
- Motor DTP1/54 has an rpm range of 600 to 1750.
- Motor DTP1/56 has an rpm range of 600 to 1150.
- Motor EP0026 has an rpm range of 600 to 1150.
- Motor GP0014 has an rpm range of 600 to 1800.
- Motor GP0016 has an rpm range of 600 to 1150.
- Motor GP0024 has an rpm range of 600 to 1740.
- Motor GP0024-50 has an rpm range of 600 to 1440.
- Motor GP0026 has an rpm range of 600 to 1150.
- Motor GP0034 has an rpm range of 600 to 1800.
- Motor GP0034-50 has an rpm range of 600 to 1440.
- Motor GP1/54 has an rpm range of 600 to 1800.
- Motor GP1/56 has an rpm range of 600 to 1150.
- Motor NP0024 has an rpm range of 600 to 1740.
- Motor NP0026 has an rpm range of 600 to 1150.
- Motor NP0034 has an rpm range of 600 to 1755.

Performance shown is certified for Installation Type A: Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances in the airstream. The sound ratings shown are loudness values in fan sones at 5 ft (1.5m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for Installation Type A: Free inlet hemispherical sone levels.