

Hotpoint® PTAC with Electric Heat 230/208V, 20amp *Model# AH12E09D3B*

Photo Not Available

FEATURES	
Control Type	Electronic
Fan Speed Selections	3 Cooling 3 Fan Only 3 Heating
Discharge Grille	2-position
Product Type	Packaged Terminal Air Conditioners (PTAC)
Refrigerant Type	R410A
Manual Vent Control	Hidden
"SmartFan" Fan Cycle	Yes
Chassis Type	Slide-In
Fan Motor	2
Unit Features	Auto Power Recovery Automatic Indoor Frost Control Central Desk Control Compatibility Freeze Sentinel Power Cord (LCDI) included Remote Thermostat Compatibility
Temperature Range	62 - 80 F
Heat - Cool	Yes
Auto Power Recovery	Yes
Rotary Compressor	Yes
Outdoor Vent / Exhaust	Yes
Venting Features	Concealed Manual Vent Control Vent Air Filter
Heating System	Electric Resistance

Have more questions? Please contact 1-800-626-2000



Hotpoint® PTAC with Electric Heat 230/208V, 20amp *Model# AH12E09D3B*

APPROXIMATE DIMENSIONS(HxDxW)

16 H x 42 2/5 W x 20 9/10 D

CAPACITY

- Cooling BTUH (MAX) 9200.000000Btu
- CFM Indoor Fan Low 340
- CFM Indoor Fan Medium 391
- CFM Indoor Fan High 434
- Cooling EER (BTUH / Watt) 11.3
- Cooling BTUH (MIN) 9000.0Btu

APPEARANCE

- Installation Through-the-Wall
- Color Appearance White

WEIGHTS & DIMENSIONS

- Overall Width (in) 42 2/5in
- Approximate Shipping Weight (lb) 109lb
- Overall Height (in) 16in
- Overall Depth (in) 20 9/10in
- Net Weight (lb) 98lb

POWER / RATINGS

- Cooling Amperes 3.5/3.8
- Cooling Watts 810/795
- Voltage (MIN) 208.0V
- Heating Electric Heater Watts 3535/2900
- Voltage (MAX) 230.000000V
- Heating Electric Heater Amps 15.3/13.7

WARRANTY

- · Warranty Notes See written warranty for full details
- Labor Warranty Limited 1-year entire appliance Limited 5-year sealed refrigerating system
- Parts Warranty Limited 1-year entire appliance Limited 5-year sealed refrigerating system

CERTIFICATIONS

 Claims & Certifications - AHRI CSA CUL UL NRCAN

Have more questions? Please contact 1-800-626-2000