



Hotpoint® PTAC Heat Pump 230/208V, 20amp  
Model# AH12H07D3B

*Photo Not Available*

**FEATURES**

|                        |  |
|------------------------|--|
| Control Type           | Electronic   |
| Fan Speed Selections   | 3 Cooling<br>3 Fan Only<br>3 Heating   |
| Discharge Grille       | 2-position   |
| Product Type           | Packaged Terminal Air Conditioners (PTAC)  |
| Refrigerant Type       | R410A  |
| Manual Vent Control    | Hidden   |
| "SmartFan" Fan Cycle   | Yes  |
| Chassis Type           | Slide-In   |
| Fan Motor              | 2  |
| Heat Pump              | Yes  |
| Unit Features          | Auto Power Recovery<br>Automatic Emergency Heat<br>Automatic Indoor Frost Control<br>Central Desk Control Compatibility<br>Freeze Sentinel<br>Heat Pump with Resistance Heat Backup<br>Power Cord (LCDI) included<br>Remote Thermostat Compatibility |
| Temperature Range      | 62 - 80 F  |
| Heat - Cool            | Yes  |
| Auto Power Recovery    | Yes  |
| Rotary Compressor      | Yes  |
| Outdoor Vent / Exhaust | Yes  |
| Venting Features       | Concealed Manual Vent Control<br>Vent Air Filter   |
| Heating System         | Heat Pump with Resistance Backup   |

Have more questions? Please contact 1-800-626-2000



## Hotpoint® PTAC Heat Pump 230/208V, 20amp Model# AH12H07D3B

---

### APPROXIMATE DIMENSIONS(HxDxW)

- 16 H x 42 2/5 W x 20 9/10 D

### CAPACITY

- Cooling BTUH (MAX) - 7200.000000Btu
- CFM Indoor Fan Low - 240
- CFM Indoor Fan Medium - 281
- CFM Indoor Fan High - 335
- Cooling EER (BTUH / Watt) - 11.9
- Heating - Reverse Cycle - BTUH - 6000/5800
- Cooling BTUH (MIN) - 6800.0Btu

### APPEARANCE

- Installation - Through-the-Wall
- Color Appearance - White

### WEIGHTS & DIMENSIONS

- Overall Width (in) - 42 2/5in
- Approximate Shipping Weight (lb) - 116lb
- Overall Height (in) - 16in
- Overall Depth (in) - 20 9/10in
- Net Weight (lb) - 105lb

### POWER / RATINGS

- Heating - Reverse Cycle - Watts - 515/500
- Cooling - Amperes - 2.4/2.6
- Cooling - Watts - 605/570
- Heating - Reverse Cycle - Amps - 2.22/2.38
- Voltage (MIN) - 208.0V
- Heating - Electric - Heater Watts - 3535/2900
- Heating - Reverse Cycle - COP - 3.4
- Voltage (MAX) - 230.000000V
- Heating - Electric - Heater Amps - 15.3/13.7

### WARRANTY

- Warranty Notes - See written warranty for full details
- Labor Warranty - Limited 1-year entire appliance  
Limited 5-year sealed refrigerating system
- Parts Warranty - Limited 1-year entire appliance  
Limited 5-year sealed refrigerating system

### CERTIFICATIONS

- Claims & Certifications - AHRI  
CSA  
CUL  
UL  
NRCAN