

Hotpoint® PTAC Heat Pump Unit with Electric Heat Backup 265V, 20amp Model# AH12H12E3B

Photo Not Available

FEATURES	
Control Type	Electronic
Fan Speed Selections	3 Cooling 3 Fan Only 3 Heating
Discharge Grille	2-position
Product Type	Packaged Terminal Air Conditioners (PTAC)
Refrigerant Type	R410A
Manual Vent Control	Hidden
"SmartFan" Fan Cycle	Yes
Chassis Type	Slide-In
Fan Motor	2
Heat Pump	Yes
Unit Features	Auto Power Recovery Automatic Emergency Heat Automatic Indoor Frost Control Central Desk Control Compatibility Freeze Sentinel Heat Pump with Resistance Heat Backup Power Cord included Remote Thermostat Compatibility Sub-Base required
Temperature Range	62 - 80 F
Heat - Cool	Yes
Auto Power Recovery	Yes
Rotary Compressor	Yes
Outdoor Vent / Exhaust	Yes
Venting Features	Concealed Manual Vent Control Vent Air Filter
Heating System	Heat Pump with Resistance Backup

Have more questions? Please contact 1-800-626-2000



Hotpoint® PTAC Heat Pump Unit with Electric Heat Backup 265V, 20amp Model# AH12H12E3B

APPROXIMATE DIMENSIONS(HxDxW)

16 H x 42 2/5 W x 20 9/10 D

CAPACITY

- Cooling BTUH (MAX) 12000.000000Btu
- Cooling EER (BTUH / Watt) 10.5
- Heating Reverse Cycle BTUH 10800

APPEARANCE

- Installation Through-the-Wall
- Color Appearance White

WEIGHTS & DIMENSIONS

- Overall Width (in) 42 2/5in
- Approximate Shipping Weight (lb) 127lb
- Overall Height (in) 16in
- Overall Depth (in) 20 9/10in
- Net Weight (lb) 113lb

POWER / RATINGS

- Heating Reverse Cycle Watts 989
- Cooling Amperes 4.31
- Cooling Watts 1142
- Heating Reverse Cycle Amps 4.3
- Heating Electric Heater Watts 3500
- Heating Reverse Cycle COP 3.2
- Voltage (MAX) 265.000000V
- Heating Electric Heater Amps 13.46

WARRANTY

- Warranty Notes See written warranty for full details
- Labor Warranty Limited 1-year entire appliance Limited 5-year sealed refrigerating system
- Parts Warranty Limited 1-year entire appliance Limited 5-year sealed refrigerating system

CERTIFICATIONS

 Claims & Certifications - AHRI CSA CUL UL NRCAN

Have more questions? Please contact 1-800-626-2000