

Model 4200

Direct Fired Heater



- May be ducted up to 400 feet
- Safe monitoring of combustion, two trial electronic ignition with 20 second pre-purge time delay and 7 second shutdown
- Fused disconnect switch permits easy, safe 100% power shut-off
- Hi limit switch protects heater by shutting down if unit is being overfired
- Motor overload/manual reset protects heater by shutting down if voltage is too low
- Panel mounted voltage meter
- Remote thermostat automatically cycles the heater high - low to maintain room temperature



**SOLD
EXCLUSIVELY BY**
heat wagon

SPECIFICATIONS

Input	4210 - 5,000,000 BTU/Hr 4215 - 6,000,000 BTU/Hr 4220 - 7,000,000 BTU/Hr
Fuel	Vapor & Liquid Propane/Natural Gas
Gas Consumption	4210 - 54.6 GPH Propane/5000 CFH NG 4215 - 65.6 GPH Propane/6000 CFH NG 4220 - 76.5 GPH Propane/7000 CFH NG
Gas Connection	3/4" FNPT - NG/Vapor Propane 1/2" FNPT - Liquid Propane
Electrical	4210 - 208-240V 1Ø 60 Amp, 208-240V 3Ø 40 Amp 4215 - 208-240V 3Ø 50 Amp, 480V 3Ø 30 Amp 4220 - 208-240V 3Ø 60 Amp, 480V 3Ø 40 Amp
Fan	4210 - 27,500 CFM, 10 HP 4215 - 33,500 CFM, 15 HP 4220 - 40,100 CFM, 20 HP
Duct (optional)	WD3025HT
Thermostat	High - Low
Temp Rise	200°F
Dimensions	99"L x 64"W x 78"H
Weight	4210 - 1,140 lbs. 4215 - 1,250 lbs. 4220 - 1,350 lbs.

MODEL CHART

Model	Fuel	Power
4210-1	Natural Gas	1Ø 240V
4210-2	Natural Gas	3Ø 240V
4210-3	Natural Gas	3Ø 480V
4210-4	Liquid Propane	1Ø 240V
4210-5	Liquid Propane	3Ø 240V
4210-6	Liquid Propane	3Ø 480V
4215-1/4220-1	Natural Gas	3Ø 240V
4215-2/4220-2	Natural Gas	3Ø 480V
4215-3/4220-3	Liquid Propane	3Ø 240V
4215-4/4220-4	Liquid Propane	3Ø 480V

Gas Supply:	Inlet Pressure		Manifold Pressure
	Max PSI	Min PSI	W.C.
Vapor Propane	250	5	9.5"
Natural	250	5	11"

For lower pressures consult Heat Wagon Tech Service



342 N. 400 E. Valparaiso, IN 46383
219-464-8818 • 219-462-7985 • www.heatwagon.com