Model VF1100SC

Indirect Fired Self-Contained Fuel Oil Heater

- More BTU's
- More CFM
- More Static Pressure
- More Fuel Efficient
- More Run Time
- · Reliable Riello burner
- · Remote thermostat with 50' cord
- Ductable up to 150 ft.
- · Convenient duct storage
- 200 gallon fuel cell with immersion heater (Double wall construction)
- Over 30 hours operating time





SPECIFICATIONS

Heater

1,000,000 BTU/Hr #1 or #2 Diesel, Kerosene 7.16 GPH Fuel Consumption 240 Volts 20 amp circuit 11,183 CFM, 1.2" S.P. Standard On/Off Thermostat 120°F @ 0°F Ambient Temp Rise

> 2 - 24" Duct Size CSA Approved Pending Riello 40 F22 Burner

85% Rated Efficiency

Generator Set

Multiquip Model DA7000 SSA
7kW Max Power
6kW Continuous Power
3600 RPM, 60 Hz AC
Kubota 2 Cylinder Engine
Liquid Cooled
Hour Meter

Trailer

RAGON

DOT Approved 2 x 3,500 Lbs. Dual Axle

4 x 15" Tires

Electric Brakes

Safety Chains, 2" Trailer Ball

Duct Storage Cabinet

200 Gallon Fuel Cell with 500 Watt

Immersion Heater

Front Screw Jack

18'L x 5'-8"W x 9'D

3,740 Lbs. (Empty)



