



## Model VG1000

- 100% clean, dry heat
- Dual fuel - switch from propane to natural gas in minutes
- Approved for indoor/outdoor applications
- Ductable to 200 ft.
- Remote thermostat with 15 ft. cord
- Compact design fits through standard doorway
- Capable of recirculation operation for proved fuel savings
- Includes flue stack



Return outlet for recirculation capability

### SPECIFICATIONS

Input	1,000,000 BTU/Hr
Fuel	Vapor Propane/Natural Gas
Gas Consumption	11 GPH Propane/1000 CFH NG
Gas Connection	1-1/4" FNPT
Electrical	240 Volts 1ø 30 amp circuit
Fan	4,075 CFM 2.0" SP
Thermostat	Standard On/Off
Temp Rise	200°F @ 0°F Ambient
Rated Efficiency	80%
Shipping Dim.	120"L x 31.5"W x 54"H
Duct Size	20" Dia. (up to 200' straight)
Approx. Weight	1,300 lbs.

Gas Supply:	Inlet Pressure	
	Max W.C.	Min W.C.
Propane	14"	9"
Natural	14"	9"



342 N. 400 E. Valparaiso, IN 46383  
 219-464-8818 • 219-462-7985 • [www.heatwagon.com](http://www.heatwagon.com)