



# heat wagon

## Model VG600A

- Switch from vapor propane to natural gas by turning one valve
- Swivel wheels included for easy maneuverability
- High efficiency combustion chamber (90%)
- Certified for inside or outside operation
- 3 modes of operation:
  - Fan only (no heat)
  - Heat control using remote thermostat with constant fan ventilation
  - Heat control and fan ventilation that cycles on/off with thermostat
- Remote thermostat with 50 ft. cord, flue stack and inlet recirculation adapter included
- Reliable Riello burner
- Low amp draw (12 amps) whisper quiet axial fan (<66 dB)
- Forklift pockets and cable lifting fixtures
- Capable of recirculation operation for improved fuel savings



### SPECIFICATIONS

Input	600,000 BTU/Hr
Fuel	Vapor Propane/Natural Gas
Gas Consumption	6.6 GPH Propane/600 CFH NG
Gas Connection	1" FNPT
Electrical	120 Volts 15 amp circuit
Fan	7063 CFM, 0.6" SP
Thermostat	Standard On/Off
Temp Rise	120°F @ 0°F Ambient
Rated Efficiency	90%
Dimensions	80"L x 36"W x 56"H
Duct Size	24"-WD2425 (up to 75' straight)
Approx. Weight	600 lbs.

Gas Supply:	Inlet Pressure	
	Max W.C.	Min W.C.
Propane	14"	8"
Natural	14"	7"

**heat wagon** 

Rev. 12-19

342 N. 400 E. Valparaiso, IN 46383  
219-464-8818 • 219-462-7985 • [www.heatwagon.com](http://www.heatwagon.com)