

Air Vents and Eliminators

GoldTop™—Universal Air Vent for Residential and Commercial Heating and Cooling Systems



The GoldTop offers a convenient, one-fits-all concept, to stock one vent for all your venting needs, between 1 and 150 psi systems. Honeywell's revolutionary patented fulcrum design offers a venting rate of 3-4 times that of other products.

- Patent No. 5,988,201.

Application: Residential or commercial heating and cooling systems
Operating Temperature Range: 240°F Maximum (115°C Maximum)
Maximum Safe Operating Pressure (psi): 150 psi
Maximum Safe Operating Pressure (kPa): 1034 kPa
Approximate, Dimensions: 1 27/32 in. diameter x 3 1/4 in. long
 (24 mm diameter x 83 mm long)
Materials: Brass

| Material Number | Connection Type | Connection Size (in.) | Weight | Description |
|-----------------|-----------------|-----------------------|------------------|--|
| FV180/U | Male NPT | 1/8 in. | 0.4 lb (0.18 kg) | 1/8 in. NPT Goldtop Universal Air Vent for heating and cooling systems |
| FV180A/U | Male NPT | 1/4 in. | 0.4 lb (0.18 kg) | 1/4 in. NPT Goldtop Universal Air Vent for heating and cooling systems |

MaxiVent™ Air Vent for Heating and Cooling Systems



The Maxivent features a low profile, fit anywhere solid brass body and cover, and a high temperature polypropylene float.

Application: Residential or commercial heating and cooling systems
Operating Temperature Range: 240°F Maximum (115°C Maximum)
Maximum Safe Operating Pressure (psi): 150 psi
Maximum Safe Operating Pressure (kPa): 1034 kPa
Approximate, Dimensions: 2 in. high x 1 5/32 in. diameter (51 mm high x 29 mm diameter)
Materials: Brass

| Material Number | Connection Type | Connection Size (in.) | Weight | Description |
|-----------------|-----------------|-----------------------|-------------------|--|
| FV147/U | Male NPT | 1/8 in. | 0.12 lb (0.06 kg) | 1/8 in. NPT Air Vent for heating and cooling systems |
| FV147A/U | Male NPT | 1/4 in. | 0.12 lb (0.06 kg) | 1/4 in. NPT Air Vent for heating and cooling systems |

AP400 Air Purger



Replacement Parts - Old Style AM Series (Aquamix)

- Heavy Duty cast iron construction
- 1 inch, 1 1/4 and 1 1/2 inch models (inlet and outlet)
- 1/2 inch bottom tapping for expansion tank mount
- 1/8 inch top tapping for air vent mount
- Directional flow arrow for correct installation

Application: Closed heating systems
Operating Temperature Range: 275°F Maximum (135°C Maximum)
Maximum Safe Operating Pressure (psi): 125 psi
Maximum Safe Operating Pressure (kPa): 862 kPa
Approximate, Dimensions: 6 in. long x 3-3/4 in. high x 2-3/8 in. wide
 (152 mm long x 95 mm high x 60 mm wide)
Materials: Cast Iron

| Material Number | Connection Type | Pipe Size (inch) | Connection Size (in.) | Weight | Description |
|-----------------|-----------------|------------------|----------------------------------|-----------------|---|
| AP400/U | Female NPT | 1 in. | Bottom: 1/2 in.; Top: 1/8 in. | 4.2 lb (1.9 kg) | 1 in. NPT Air Purger for closed heating systems |
| AP401/U | Female NPT | 1 1/4 in. | Bottom: 1/2 in.; Top: 1/8 in. | 3.8 lb (1.7 kg) | 1 1/4 in. NPT Air Purger for closed heating systems |
| AP402/U | Female NPT | 1 1/2 in. | Bottom: 1/2 in.; Top: 1/8 in. | 8.6 lb (3.9 kg) | 1 1/2 in. NPT Air Purger for closed heating systems |