






Also Available in double burner model

Contact us today for a FREE design and quote!

IL Series - Economical High Intensity Heater

Information below is intended only as a reference and should not be used when installing equipment. Please ensure you locate the most recent instruction manual for accurate and up to date information.



Optional Accessories

Flexible Gas Connector 1/2" x 24"	JL-0771-XX
#2 Lion Chain, roll 200'	JL-0800-XX
Safety Snap Hooks 2" - Package of 24	JL-0800-SH
Safety Snap Hooks 2" - Package of 100	JL-0800-SH-B

Consult your local authorized dealer for other Infrasave accessories:

- Line-voltage and 24V thermostat and controls
 Side reflector extensions








IL Series Installation Manual


IL-X 150-200 Installation Manual

IL Series Replacement Parts List

Distributor Information:

Dimensions and Specifications





D	DIMENSIONS		INPUT	WEIGHT	ELECT.
Α	В	С	BTU/HR	LBS.	
13.50"	24"	11.28"	21,500	22	
20.50"	30.25"	15.50"	35,000	26	
28.00"	38.50"	18.50"	50,000	31	24 VAC
38.75"	48.50"	29.5"	65,000	38	60 Hz
53.25"	63.75"	44"	100,000	45	0.55 A
39.75"	48.50"	36.50"	143,000	65	
54.25"	63.00"	51.00"	200,000	75	
	A 13.50" 20.50" 28.00" 38.75" 53.25" 39.75"	A B 13.50" 24" 20.50" 30.25" 28.00" 38.50" 38.75" 48.50" 53.25" 63.75" 39.75" 48.50" 54.25" 63.00"	A B C 13.50" 24" 11.28" 20.50" 30.25" 15.50" 28.00" 38.50" 18.50" 38.75" 48.50" 29.5" 53.25" 63.75" 44" 39.75" 48.50" 36.50" 54.25" 63.00" 51.00"	A B C BTU/HR 13.50" 24" 11.28" 21,500 20.50" 30.25" 15.50" 35,000 28.00" 38.50" 18.50" 50,000 38.75" 48.50" 29.5" 65,000 53.25" 63.75" 44" 100,000 39.75" 48.50" 36.50" 143,000 54.25" 63.00" 51.00" 200,000	A B C BTU/HR LBS. 13.50" 24" 11.28" 21,500 22 20.50" 30.25" 15.50" 35,000 26 28.00" 38.50" 18.50" 50,000 31 38.75" 48.50" 29.5" 65,000 38 53.25" 63.75" 44" 100,000 45 39.75" 48.50" 36.50" 143,000 65 54.25" 63.00" 51.00" 200,000 75

*Double Burner Models

Heater Controls & Thermostats



TruTemp

Infrared Setback Thermostat

- Setback reduces control temperature by 9°F [13°C] when a building is unoccupied
- Setback is activated at night time by turning off lights
- Mounts on standard 4" [10cm] electrical box or directly to wall
- Tamper-proof option

Other Thermostats Available

- Line voltage control
- 24 Vac Control
- Moisture resistant controls
- 2-stage thermostatic control

Our customers include:

























M020915 RL: v1.3 RD: Mar-2019