

HAF Stir Fan with Wide Guard

Features

- Wide guard spacing reduces build-up and allows for easy cleaning so your fan remains efficient
- Maximum air circulation with minimal power usage reducing stratification and promote uniform air temperatures

- Versatile mounting bracket allows for tilt and swivel of fan to easily change direction and angle of air movement
- Totally enclosed, maintenance-free, direct drive high-efficiency motors have completely sealed ball bearings, and are covered by a **2 Year Warranty**
- Attached 10' cord with 3-prong plug pre-wired for 115 Volts (electrician may rewire for 230 Volts)



Part#	Size	Ph	Spd	Thrust CFM	Thrust CFM/Watt	Drive	Prop
Single Phase							
VS18	18"	1	1	1,760	16.3	Direct	3-Alm
VS183	18"	1	3(H)	1,560	21.3	Direct	3-Alm
			(M)	1,460	24.8		
			(L)	1,390	24.5		
VS20	20"	1	1	1,920	20.4	Direct	3-Alm
* VS203	20"	1	1	3,710	12.4	Direct	3-Alm
VS24	24"	1	1	3,790	13.1	Direct	3-Alm
VS242	24"	1	1	5,630	12.8	Direct	3-Alm

No electrician needed!
**Hang it up
Plug it in**

- * Best sellers/recommended models
- Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 230-12**
OSHA requires this fan to be mounted a minimum of 7' above the floor

RECIRCULATION FANS

HAF Panel Fan with Wide Guard

Features

- Direct drive - no belts or pulleys to maintain
- Two options to fit your application:
 - Non-corrosive fiberglass housing with poly prop and stainless-steel hardware
 - Heavy-duty 18-gauge galvanized housing with aluminum prop
- Ships fully assembled and ready to hang
- 3 built-in mounting loops on the rear of the fan allow you to hang at an angle for greater control of the airflow
- Heavy gauge powder-coated wide guard on front and rear of fan to maximize airflow while protecting the blades
- Totally enclosed, maintenance-free, high-efficiency standard motors have completely sealed ball bearings, are UL and CUL recognized, and are covered by a **2 Year Warranty**
- IP66-Rated Gold Star Motors have a **3 Year Warranty**



Fiberglass Housing



Galvanized Housing

Part#	Size	Ph	Spd	Thrust CFM	Thrust CFM/Watt	Drive	Prop
Fiberglass Housing							
Single Phase with Gold Star Motor							
VPP20F13P-GS	20"	1	1	4,250	13.8	Direct	3-Ply
VPP24F13P-GS	24"	1	1	4,660	16.6	Direct	3-Ply
* VPP24F12P-GS	24"	1	1	6,180	12.2	Direct	3-Ply
Single Phase with Standard Motor							
VPP20F13P	20"	1	1	4,070	13.7	Direct	3-Ply
VPP24F13P	24"	1	1	4,730	17.8	Direct	3-Ply
VPP24F12P	24"	1	1	6,080	12.1	Direct	3-Ply
Galvanized Housing							
Single Phase with Gold Star Motor							
VPP20G13A-GS	20"	1	1/Var [^]	4,140	11.5	Direct	3-Alm
VPP24G13A-GS	24"	1	1/Var [^]	4,020	13.3	Direct	3-Alm
VPP24G12A-GS	24"	1	1	5,470	15.3	Direct	3-Alm
Single Phase with Standard Motor							
VPP20G13A	20"	1	1	3,430	12.8	Direct	3-Alm
VPP24G13A	24"	1	1	4,030	14.0	Direct	3-Alm
* VPP24G12A	24"	1	1	4,790	12.9	Direct	3-Alm

- * Best sellers/recommended models
- [^] Variable speed fans require separate variable speed control to adjust fan speed

Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 230-12
OSHA requires this fan to be mounted a minimum of 7' above the floor



⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.