Total System Solutions

Heavy-Duty Industrial Basket Fan with 2 & 3-Speed High-Efficiency Motors

The J&D Heavy-Duty Industrial Basket Fan sets the standard in air performance. This fan was designed for the industrial market and provides the performance that is mandatory for machine efficiency and employee comfort.

Features

- 2-speed, non-oscillating and 3-speed, oscillating high-efficiency motor with pull chain
- Attached cord with 3-prong plug pre-wired for 115 Volts
- Direct drive no belts or pulleys to maintain
- \bullet 20" and 24" models with a ¼ HP motor are available in black or white
- \bullet 30" oscillating model with a powerful $\frac{1}{2}$ HP motor is available in black
- Oscillating models feature 80° pivot range
- Heavy gauge, corrosion-resistant powder coated guards
- Guards meet OSHA 1910.212(a)(5) requirements allowing this fan to be installed at any height
- Totally enclosed, maintenance-free, high-efficiency motors feature sealed ball bearings and are covered by a **2 Year Warranty**
- Compatible with our misting/fogging product line
- Optional wall or post mount brackets

MOUNTING BRACKETS ARE NOT INCLUDED

Select from the recommended brackets below to fit your installation needs.

Part #	Description	Powder Coated Black	Dip			
Side Mount Brackets						
VRSBR14	42" Extended Bracket, fits Sq. or Round Up Post	Х				
VRSBR143	42" Extended Bracket, fits 3" Tube - Bolt On	Х				
VRSBR144	42" Extended Bracket, fits 4" Tube – Bolt On	Х				
VRSBR14412	42" Extended Bracket, 4½" Tube – Bolt On	Х				
VRSBR901-HDG	Wall Mount Bracket		Х			





Shown: VRSBR901-HDG wall mount bracket with oscillating fan



					Thrust	Thrust CFM/		
	Part#	Size	Ph	Spd	CFM	Watt	Drive	Prop
	Single Phase							
	Non-Oscillati		ack					
	VDF20HOB2	20″	1		2,550		Direct	3-Alm
					1,900	12.7		
	VDF24H0B2	24″	1		3,700	15.5	Direct	3-Alm
					2,050	13.0		
	Non-Oscillati							
	VDF20HOW2	20″	1		2,550	13.3	Direct	3-Alm
					1,900	12.7		
*	VDF24HOW2	24″	1		3,700	15.5	Direct	3-Alm
					2,050	13.0		
	Oscillating Bl		1					
	VDF201HOB2	20″	1		2,340	13.0	Direct	3-Alm
					2,280	20.4		
					2,250	23.2		
	VDF241HOB2	24″	1		3,820	15.7	Direct	3-Alm
					3,350	20.2		
					3,050	21.5		
	VDF301HOB2	30″	1		6,520	14.0	Direct	3-Alm
					6,060	14.9		
				(L)	4,970	13.2		
	Oscillating W							
	VDF201HOW2	20″	1		2,340	13.0	Direct	3-Alm
				(M)		20.4		
					2,250	23.2		
	VDF241HOW2	24″	1		3,820	15.7	Direct	3-Alm
					3,350	20.2		
	* Post collors/r			·	3,050	21.5		

* Best sellers/recommended models

Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 230-12

▲WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.