
# **Mega Fan Series**

### 72" Fiberglass Exhaust Fans

Whether trying to select fans that meet requirement for energy rebates, specific ventilation requirements, or zero maintenance, J&D's Mega Fan Series of 72" Fiberglass Exhaust Fans has a model that will fit all of your exhaust fan needs.



▲ WARNING: This product can expose you to chemicals including chromium, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.




## **Mega Torque Fans**

#### **Torque Drive 72" Fiberglass Exhaust Fan**

J&D's Mega Torque fans maintain FANtastic performance and great efficiency with no power loss or reduction from aging belts and pulleys. Their premium and efficient industrial motor provide years of care free service.





Appearance of motor may very

					@ 0.10" SP				
						CFM/			
	Part #	Size	Ph	Spd	CFM	Watt	Drive	Prop	
	Mega Torque With VFD								
	Three Phase Wired for 240V								
	With 1 Piece Cone (for 3 piece cone, add H after C in part #)								
	Aluminum Shutter								
**	VMTA72A5C33E-VFD240	72"	3	1	41,437	20.4	Torque	5-Alm	
	Three Phase Wired for 480V								
With 1 Piece Cone (for 3 piece cone, add H after C in part #)									
	Aluminum Shutter								
	VMTA72A5C33E-VFD480	72"	3	1	41,437	20.4	Torque	5-Alm	
	Mega Torque								
	Three Phase								
	With 1 Piece Cone (for 3 piece cone, add H after C in part #)								
	Aluminum Shutter								
**	VMTA72A5C33E	72"	3	1	42,455	20.7	Torque	5-Alm	
	Accessories								
	VRS75 Shutter Motor Kit, for 3 Panel Aluminum Shutter								
	VRS75-C Shutter Motor Kit, for 3 Panel Aluminum Shutter w/Cord								

\*\* Best sellers of 2018-19

Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA 210-07 standard.

**NOTE:** It is **highly** recommended that a motorized shutter kit be installed to open shutter when fan is operating at 40% or lower

### **Save Time & Money**

No Belts to Change No Pulleys to Maintain No Greasing Motor or Bearings

#### **Mega Torque With VFD**

- Comes with VFD (Variable Frequency Drive)
  - Pre-wired to motor and pre-set for easy installation
  - Soft starts fan to reduce loads on fan during start up and helps to extend fan life
  - Compatible with most J&D controls
  - NEMA 4x enclosure with cooling fins, mounted in air flow to ensure low temperature during operation
  - Short wire length between motor and VFD to eliminate electrical noise and extend motor life
  - Pre-installed filters to eliminate interference with RFID readers and other electronics
- 3 Year Warranty on motor and torque drive

#### **Mega Torque**


- VFD (Variable Frequency Drive) compatible and recommended (VFD not included)
- Motorized shutter kit compatible highly recommended when fan is operating at 40% or lower
- 1 Year Warranty on motor and torque drive

Extend motor and torque drive warranty to 3 Years by pairing with the J&D Pilot Control System or upgrade to the Mega Torque with mounted VFD

▲ WARNING: This product can expose you to chemicals including chromium, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.

## **Mega Storm Fans**

#### Belt Drive 72" Fiberglass Exhaust Fan



Shown: Mega Storm II (Mega Storm motor belt tensioner appearance and locations differ)

- Twin Gates® size "A" belts are easily accessible and require no tools for replacement in seconds
- Double groove steel belt tensioner for longer life
- 1½" shaft and sealed pillow block bearings
- 3 Year Warranty on bearings



					0.0.40//.00					
					@ 0.10" SP					
		٠.				CFM/	l	_		
	Part #	Size	Ph	Spd	CFM	watt	Drive	Prop		
	Mega Storm II									
	Three Phase									
With 1 Piece Cone (for 3 piece cone, add H after C in pa										
	Aluminum Shutter									
	VMA72A5C33	72"	3	1	39,270		Belt	5-Alm		
	VMA72A5C33-E		3	1	40,121		Belt	5-Alm		
**	VMA72A5C33-H	72"	3	1	48,264	18.2	Belt	5-Alm		
	Mega Storm									
	Single Phase									
	No Cone									
	<b>Aluminum Shu</b>	tter								
	VMSA72A5N31	72"	1	1	38,960	14.9	Belt	5-Alm		
	With 1 Piece C	one (	for 3	3 piece	cone, add	H after C	in part	#)		
	<b>Aluminum Shu</b>	tter								
**	VMSA72A5C31	72"	1	1	40,792	15.7	Belt	5-Alm		
	Three Phase									
	No Cone									
	<b>Aluminum Shu</b>	tter								
**	VMSA72A5N33	72"	3	1	42,950	14.3	Belt	5-Alm		
	With 1 Piece C	one (	for 3	piece	cone, add	H after C	in part	#)		
	Aluminum Shutter									
	VMSA72A5C33	72"	3	1	44,734	14.9	Belt	5-Alm		

\*\* Best sellers of 2018-19

Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA 210-07 standard.

#### **Mega Storm II Features**

- 48,264 CFM @.10"SP high performance model available
- High efficiency model that exceed 21 CFM/Watt
- 3 Year Warranty on Energy efficient (-E) and High efficient (-H) motors

#### **Mega Storm Features**

- Certified performances up to 41,029 CFM @.10" SP
- Single or three phase 3 HP, UL recognized motors
- 2 Year Warranty on motors



▲ WARNING: This product can expose you to chemicals including chromium, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.