# **Poly Stormer**

Keep air moving efficiently across your facility with J&D's Poly Stormer. Made with high CFM in mind, this economical fan will give you the efficiency you want and the airflow you deserve.

### **Features**

- Fan ships fully assembled
- Direct drive motor with no belts or bearings to maintain
- Totally enclosed, maintenance-free, high-efficiency standard motors have completely sealed ball bearings, are UL and CUL recognized, and are covered by a 2 Year Warranty
- Gold Star Motors have a **3 Year Warranty**
- Polyethylene housing will not rust or corrode
- Stainless-steel fasteners, powder coated guards, and galvanized prop for long lasting corrosion-resistance
- Lightweight for easier installation

Size Ph Spd CFM

1

- Motors have built-in automatic thermal overload protection for the longest motor life possible
- Compatible with our misting/fogging product line

Thrust

Thrust

CFM/

1 8,210 16.3 Direct 3-Glv

3 1 8,460 18.7 Direct 3-Glv

Watt Drive Prop

		a		
			J&D= nutacturing	1
-				
		Ŋ	1	
9	S.			

All Poly Stormer Fans include a hot dip galvanized mounting bracket

ards Me

OSHA

auireme

			_					FEATUR		
	Part#	Size	Ph	Spd	Thrust	Thrust CFM/ Watt		GOLD STAT MOTOR Prop		
	Single Phase									
	VPS36A-GS	36″	1	1	8,450	17.1	Direct	3-Glv		
	<b>Three Phase</b>	)								
*	VPS36CF-GS	36″	3	1/Var^	8,560	18.9	Direct	3-Glv		

\* Best sellers/recommended models

Variable speed fans require separate variable speed control to adjust fan speed
Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 230-12
OSHA requires this fan to be mounted a minimum of 7' above the floor

Part#

**Single Phase** 

VPS36A 36"

Three Phase VPS36CF 36"

## **High Output Deluxe Basket Fan**

J&D Manufacturing's High Output Deluxe Basket Fan series combines high performance, economical pricing, and energy efficiency to give you one of the best valued fan series available on the market today.

## **Features**

Part# Single Phase

VDB20-GS

VDB24-GS

VDB30-GS

VDB36-GS

No Cord

**Three Phase** 

VDB303-GS 30"

VDB363-GS 36"

- Fan ships completely assembled
- Direct drive no belts or pulleys to maintain
- Heavy gauge, corrosion-resistant, black powder coated guards
- Single phase models include attached cord with 3-prong plug pre-wired for 115 Volts

Thrust

CFM

3,920

5,680

6,380

9,160

6,380

9,810

With Cord (pre-wired for 115V, electrician may rewire for 230V)

1

1

Thrust CFM/

8.9

11.3

12.4

17.4

13.7

17.7

Watt Drive Prop

Direct

Direct

Direct

Direct 3-Glv

Direct 3-Alm

Direct 3-Alm

• Guards meet OSHA 1910.212(a)(5) requirements allowing this fan to be installed at any height

Size Ph Spd

1 1

3

3

20" 1 1

24″ 1

30"

36″ 1 1

 Totally enclosed, maintenance-free, high-efficiency motors feature sealed ball bearings and are covered by a

#### 2 Year Warranty

- Gold Star Motors have a **3 Year** Warranty
- Compatible with our misting/fogging product line

D 1.#	0.	DI.		Thrust	- /				
Part#		Ph	Spd	CFM	Watt	Drive	Prop		
Single Phase									
With Cord (pre-wired for 115V, electrician may rewire for 230V)									
VDB20	20″	1	1	3,340	9.1	Direct	3-Alm		
VDB24	24″	1	1	5,370	10.8	Direct	3-Alm		
VDB30	30″	1	1	6,500	11.4	Direct	3-Alm		
VDB36	36″	1	1	9,520	17.3	Direct	3-Glv		
Three Phase									
No Cord									
VDB303	30″	3	1	6,730	13.0	Direct	3-Alm		
* VDB363	36″	3	1	9,500	19.4	Direct	3-Glv		

All High Output Deluxe Basket Fans include a hot dip galvanized mounting bracket

\* Best sellers/recommended models Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 230-12

3-Alm

3-Alm

3-Alm

▲WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.