

Confined Space Ventilator

J&D Manufacturing's positive pressure Confined Space Ventilator provides fresh air in confined spaces such as manholes, crawl spaces, attics, tanks, and trailers. The Confined Space Ventilator includes the patented heavy-duty Diamond Brite™ circulation fan and flexible high visibility ducting to direct the air exactly where you need it.

Fan Features

- Patented heavy-duty aluminum Diamond Brite™ fan housing (Pat. No. Des. 509,582)
- 8-bladed, high output, poly propeller performs under heavy static pressure
- Direct drive - no belts or bearings to maintain
- Convenient cord wrap for storage and transportation
- Rubber feet for reduced noise and stable operation
- Poly handles for easy moving and carrying
- Attached cord with 3-prong plug pre-wired for 115 Volts
- Heavy gauge, corrosion-resistant, powder coated wire fan guards meet OSHA 1910.212(a)(5) requirements
- High-efficiency motor is totally enclosed and maintenance-free with sealed ball bearings and a **2 Year Warranty**
- Fan ships completely assembled and ready for use



Duct Features

- 20" diameter ducting expands from 18" to 20' fully extended
- High visibility safety yellow fabric with reinforced segments
- Made from flame-retardant fabric thermally sealed to an ASTM approved helical wire
- Cuff and adjustable clasp to secure ducting to fan for quick installation

Part#	Size	Ph	Spd	Thrust CFM	Thrust CFM/ Watt	Drive	Prop
Single Phase							
Fan with 20' of Ducting							
VICS20-GLB	20"	1	1	3,025	3.0	Direct	8-Ply
Fan Only							
VICS20	20"	1	1	3,780	3.9	Direct	8-Ply
Duct Only							
VICSDUCT20	22"W x 20'L, Flexible Ducting Safety Yellow w/Adjustable Belt						

Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 230-12

24" Premium Direct Drive Drum Fan

Features

- Sleek, black powder coated steel housing and cart with sturdy wheels and handles for easy transportation
- 2-speed dial to switch from LOW to HIGH speed
- Direct air exactly where you need it by tilting fan
- Attached 10' cord with 3-prong plug pre-wired for 115 Volts
- Convenient cord wrap to store cord when not in use
- Direct drive and quiet operation
- Guards meet OSHA 1910.212(a)(5) requirements for use at any height
- Fan is UL/CUL listed (File #E144918)
- Totally enclosed, maintenance-free, high-efficiency motors have completely sealed ball bearings and are covered by a **1 Year Warranty**
- Fan ships completely assembled and ready for use



**HIGH/LOW
Two-Speed Dial**



**Stow Away
Cord Wrap**



**Fan Tilt
Adjustment Knob**



Part#	Size	Ph	Spd	Thrust CFM	Drive	Prop
Single Phase						
PDF24	24"	1	2(H) (L)	7,760 5,500	Direct	3-Alm

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.