# Thread Sealant

#### **Comparison Chart**











**WOG Plus** 

Steel-Unyte

Tru-Blu

Gasolia Hard Set

Hercules Grrip

The Heavyweight Select-Unyte

Blue Monster PTRE

Pipe Thread Sealant

T+2

Gasoila Soft-Set

Thread Sealant PTFE

TFE Paste

Real-Tuff

**Green Stuff** T-U Type 555

Blue Monster

#5, #5 Special, #5 Sub-Zero

Thread Sealant

Gasoila-NT

Yellow Sealant

White Stuff Select-Unyte

Blue Monster PTRE Pipe Thread Sealant

T+2

Gasoila Soft-Set Thread Sealant PTFE

TFE Paste

Real-Tuff

**Great White** White Seal

Copper **Anti-Seize** Talon Copper

Blue Monster Copper Anti-Seize Lubricant

Copper-Rich

**Nickel Anti-Seize** 

Talon Nickel Blue Monster Nick-

el Anti-Seize

Nickel-Rich

Gasolia Thred Gard

IPS

Diesel Fuel Oil

Fatty Acids (Liquids)

JC Whitlam

Blue

Monster

Rectorseal

Federal

**Process** 

Harvey

Hercules

Oatey

**Great White** White Seal

Oatey Great Blue

Green Stuff

					Uses	Ck	ar	+						
						_	-	-						
Acetylene					Freon (All)						Natural Gas			
Acids, Diluted					Gasoline*						Nitrogen, Gaseous			
Air, Compressed Gaseous					Gasohol						Oxygen			
Alkalis Diluted					Glycol						Petroleum Solvents			
Ammonia					Heating Oils						Propane			
Aliphatic Solvents					Helium Gaseous						Refrigeration Gases			
Brine					Hydraulic Oils						Soap, Liquid			
Butane					Hydrogen						Steam Lines			
Carbon Dioxide					Inert Gases, Gaseous						Sugar, Liquid			
Castor Oils					Jet Fuel (JP 3,4,5)						Vegetable Oils			
<b>Chlorinated Water</b>					Kerosene						Water (Hot or Cold)			
Corrosives					Lacquer						Xylol			
Coal Tar Naphtha	•	•	•		Liquefied Petroleum Gases	•	•	•	•					
Cutting Oils					Manufactured Gases									

<sup>\*</sup> Heavyweight, Green Stuff, and White Stuff are compatible with fuel blends up to E15 (15% ethanol content)

Mineral Oils

Naphtha 🌢

### **Thread Sealant**

## PMAIN VALVE

#### **Green Stuff**

**Slow-Drying Soft-Set General Purpose Thread Sealant** 

Part No.	Size	Case	Weight
400-101	2 oz tube	72	11
400-102	4 oz can	24	13
400-103	8 oz can	24	20
400-104	16 oz can	12	22
400-105	32 oz can	12	39

Green Stuff is a slow drying, soft setting, non-hardening pipe thread compound. It will not transfer taste or odor to the system being sealed. Excellent for food and water systems. It is lead free, anti-galling, non-corrosive, nontoxic and will not harden in can.





#### **White Stuff**

Slow-Drying Soft-Set PTFE Thread Sealant

Part No.	Size	Case	Weight
400-001	2 oz tube	72	11
400-002	4 oz can	24	13
400-003	8 oz can	24	20
400-004	16 oz can	12	22
400-005	32 oz can	12	39

White Stuff is a slow drying, soft setting, non-hardening PTFE pipe thread compound. It will not transfer taste or odor to the system being sealed. Excellent for food and water systems. It is lead free, anti-galling, noncorrosive, nontoxic and will not harden in can.





#### Heavyweight

Slow-Drying Soft-Set Extra PTFE Thread Sealant

Part No.	Size	Case	Weight
400-202	4 oz can	24	13
400-203	8 oz can	24	20
400-204	16 oz can	12	22
400-205	32 oz can	12	39

Heavyweight is a slow drying, soft setting, non-hardening industrial PTFE pipe thread compound. It will not transfer taste or odor to the system being sealed. Excellent for food and water systems. It is lead free, anti-galling, non-corrosive, nontoxic and will not harden in can.



#### **WOG Plus**

Fast-Drying Hard-Set Thread and Gasket Sealant

<u> </u>			-
Part No.	Size	Case	Weight
400-302	4 oz can	24	12
400-303	8 oz can	24	21
400-304	16 oz can	12	19
400-305	32 oz can	12	38

W.O.G Plus is a fast drying, hard setting, semipaste, thread and gasket sealer. It remains flexible, so vibrations will not loosen connection. W.O.G. Plus seals tightly but allows for disassembly without damage to parts. It is lead free, halogen free, non-corrosive and nontoxic.



#### **Copper Anti-Seize**

High Temperature Anti-Seize Lubricant and Thread Sealant

Part No.	Size	Case	Weight
400-403	8 oz can	24	19
400-404	16 oz can	12	15

Copper Anti-Seize is a copper based anti-seize lubricant and thread sealant. It produces a permanent leak-proof metallic seal under pressure, yet prevents seizing, galling, freezing, and tearing, even under extreme conditions. It is lead free, non-corrosive, nontoxic and will not harden in can.



#### **Nickel Anti-Seize**

**High Temperature Anti-Seize Lubricant and Thread Sealant** 

Part No.	Size	Case	Weight
400-503	8 oz can	12	10
400-504	16 oz can	12	19

Nickel Anti-Seize is a non-seizing, nickel based, lubricant and thread sealant. It may be used to prevent seizing, corrosion and galling where extreme temperature conditions exist. Contains a high percentage of micro-fine nickel flakes and is fortified with high quality rust and corrosion inhibitors. It is lead free, nontoxic, and will not harden in can.

