

# Architectural Heater KAWH Series



### Model Code:

KAWH	20	20	1	BW	TAV
A	B	C	D	E	F
A: Series					
B: 12 - 120V 20 - 208V					
24 - 240/208V					
27 - 277V 48 - 480V					
C: Watts (1125 to 8000)					
D: 1 - 1Phase 3 - 3Phase					
E: Grill Color					
F: TAV-Built-In tamper proof stat					
G: Mounting Box (Optional)					

- Tubular finned element
- Fully enclosed, factory-lubricated motor
- SureStop™ auto reset limit protection
- Bottom air outlet

- Extruded aluminum grill
- Standard color: white
- 10" minimum clearance
- 160 CFM fan (size A)

- 120, 208, 240/208, 277 or 480 Volts
- Built-in tamperproof thermostat
- Standard 140°F wiring
- 3-year limited warranty



## The Architectural Heater

The KAWH provides heavy duty elegance in an architectural heater. Designed to provide quick heat in areas affected by cold drafts. Its corrosion-resistant aluminum front is offered in several colors to blend in with any décor. Includes a built-in tamperproof thermostat, making it ideal for high-traffic areas. Powered by a fully-enclosed lubricated motor, the fan blows warm air downward to create increase air circulation. Excellent for use in apartment complexes, commercial buildings, entryways, stairwells or garages.

**Ordering Information** Standard Color is White. Refer to grill options chart for alternate colors. \*\*Built-In tamper proof thermostat included.

MODEL **	UPC	VOLTS	PHASE	WATTS	AMPS	CFM	SIZE	SHIP WEIGHT lbs
KAWH1215-1-BW-TAV	55351	120	1	1500	12.5	160	A	24
KAWH2020-1-BW-TAV	30800	208	1	2000	9.6	160	A	24
KAWH2040-1-BW-TAV	30802	208	1	4000	19.2	160	A	24
KAWH2048-1-BW-TAV	30804	208	1	4800	23.1	160	A	24
KAWH2080-1-BW-TAV	30806	208	1	8000	38.4	320	B	50
KAWH20120-1-BW-TAV	55354	208	1	12000	5.8	480	C	90
KAWH2415-1-BW-TAV	30808	240/208*	1	1500/1125*	6.3/5.4*	160	A	24
KAWH2420-1-BW-TAV	30810	240/208*	1	2000/1500*	8.3/7.2*	160	A	24
KAWH2430-1-BW-TAV	30812	240/208*	1	3000/2250*	12.5/10.8*	160	A	24
KAWH2440-1-BW-TAV	30814	240/208*	1	4000/3000*	16.7/14.4*	160	A	24
KAWH2448-1-BW-TAV	30816	240/208*	1	4800/3600*	20.0/17.3*	160	A	24
KAWH2460-1-BW-TAV	30818	240/208*	1	6000/4500*	25.0/21.6*	320	B	50
KAWH2480-1-BW-TAV	30820	240/208*	1	8000/6000*	33.3/28.8*	320	B	50
KAWH24120-1-BW-TAV	55359	240/208*	1	12000/9000*	50.0/43.3*	320	B	90
KAWH2715-1-BW-TAV	30822	277	1	1500	5.4	160	A	24
KAWH2720-1-BW-TAV	30824	277	1	2000	7.2	160	A	24
KAWH2730-1-BW-TAV	30826	277	1	3000	10.8	160	A	24
KAWH2740-1-BW-TAV	30828	277	1	4000	14.4	160	A	24
KAWH2748-1-BW-TAV	30830	277	1	4800	17.3	160	A	24
KAWH2760-1-BW-TAV	30832	277	1	6000	21.7	320	B	55
KAWH2780-1-BW-TAV	30834	277	1	8000	28.9	320	B	55
KAWH27120-1-BW-TAV	55360	277	1	12000	43.3	480	C	90
KAWH4815-1-BW-TAV	30836	480	1	1500	3.1	160	A	28
KAWH4820-1-BW-TAV	30838	480	1	2000	4.2	160	A	28
KAWH4830-1-BW-TAV	30840	480	1	3000	6.3	160	A	28
KAWH4840-1-BW-TAV	30842	480	1	4000	8.3	160	A	28
KAWH4848-1-BW-TAV	30844	480	1	4800	10.0	160	A	28
KAWH4860-1-BW-TAV	30846	480	1	6000	12.5	320	B	55
KAWH4880-1-BW-TAV	30848	480	1	8000	16.7	320	B	55
KAWH48120-1-BW-TAV	55363	480	1	12000	25.0	480	C	90
KAWH48120-3-BW-TAV	55364	480	3	12000	14.4	480	C	90
KAWH2040-3-BW-TAV	55352	208	3	4000	11.1	160	A	28
KAWH2060-3-BW-TAV	55353	208	3	6000	16.6	480	B	90
KAWH2090-3-BW-TAV	55354	208	3	9000	24.9	480	C	90

