

Temporary Climate Control Solutions for Commercial Applications

		AVAILABLE VOLTAGES										OPTIONS AND ACCESSORIES																												
		115-1-60	208/230-1-60	208/230-3-60	460-3-60	575-3-60	ELECTRIC HEAT	REMOTE THERMOSTAT	CAMLOCK POWER CONNECTIONS	DEHUMIDIFICATION MODE	HEAT PUMP MODE	PORTABLE KIT - MODE	SIGHT GLASS	CIRCUIT BREAKER	FORK LIFT SKIDS	CONDENSER INLET DUCT ADAPTOR	HOT GAS BYPASS	VFD (Up to 3" ESP)	HOUR METER	TENT CLAMPS	DIRECTIONAL DISCHARGE GRILL	16" DUCT ADAPTOR	DUCT ADAPTOR EVAP & CONDENSER	CONDENSER DISCHARGE KIT	CONDENSATE RETURN AIR DUCT 12-INCH	RACK MOUNTING KIT	STACKING KIT	HANGING KIT	EXHAUST KIT	HOSE KIT - 9X INCHES	HOSE KIT - 18" STANDARD	REMOTE CONTROL								
CC & KK Series		Capacity (BTUH)		1 - 7.5 Ton, Indoor, Air-Cooled, Air Conditioning																																				
6CC10BEA	10,000	S																																S	O	O	O	O	S	O
6KK14BEA	13,000	S																																					S	O
6KK17BGA	16,800	S																																					S	O
6KK21BGA	21,000		S																																				S	O
5KK30BGA	29,000		S																																				S	O
6KK37BFA	37,000		S																																				S	O
6KK61BFA	61,000		S																																				S	O
6KK92BCA	92,000				S																																		S	O
SS Series		Capacity (BTUH)		Split Portable Air Conditioner																																				
6SS12BEA	12,000	S																																						
6SS24BEA	24,000		S																																					
HK Series		Capacity (BTUH)		Air-Cooled Heat Pump																																				
6HK16BEHO	18,500 Htg 16,800 Clg	S																																						
HPKW5N	66,000 Htg 60,000 Clg		S	O	O																																			
HKW Horizontal Portable Series		Capacity (Tons)		3 - 30 Ton, Horizontal Indoor & Outdoor, Air-Cooled, Air Conditioning & Dehumidifier																																				
HKW3N	3		S	O	O																																			
HKW5N	5		S	O	O																																			
HKW12M	12			S	O																																			
HKW20	20			S	O																																			
HKW25	25			S	O																																			
HKW30	30			S	O																																			
HKW Trailer Mounted Series		Capacity (Tons)		20, 25 & 30 Ton, Trailer Mounted, Air-Cooled, AC Units (US DOT Rated/Approved including Hydraulic Brakes, Dual Axle, Leveling Jacks & Spare Tire)																																				
HKW20 - TR	20			S	O																																			
HKW25 - TR	25			S	O																																			
HKW30 - TR	30			S	O																																			
KWV Vertical Portable Products		Capacity (Tons)		5, 10 & 20 Ton Vertical AC Units																																				
KWV-5	5			O	S	O																																		
KWV-10	10			S	O																																			
KWV-20	20			S	O																																			
KWH Portable Electric Heating Products		Capacity (kW)		15kW - 150kW, Horizontal, Electric Heaters with Blower																																				
KWHH15	15			S	O	O	S																																	
KWHH30	30			S	O	O	S																																	
KWHH45	45			S	O	O	S																																	
KWHH60	60			S	O	O	S																																	
KWHH150	150			S	O		S																																	
KWIB Horizontal InLine Blower		Capacity (Cfm)		Horizontal InLine Blower - 5,000 CFM																																				
KWIB5	5,000			O	S	O																																		
5WK Series AC		Capacity (BTUH)		Water-Cooled AC - 6,300 - 23,000 BTUH																																				
5WK07BEA1AAA0	6,300	S																																						
5WK14BEA1AAA0	10,800	S																																						
5WK16BEA1AAA0	16,000	S																																						
5WK18BGA1AAA0	16,100		S																																					
5WK26BGA1AAA0	23,000		S																																					
5WK Series HP		Capacity (BTUH)		Water-Cooled HP - 6,300 - 23,000 BTUH																																				
5WK07BEA1AAH0	7,000 Htg 6,300 Clg	S																																						
5WK14BEA1AAH0	12,200 Htg 10,800 Clg	S																																						
5WK18BGA1AAH0	19,100 Htg 16,100 Clg		S																																					
5WK26BGA1AAH0	27,300 Htg 23,000 Clg		S																																					

S = Standard
O = Optional

