



KAM1411

LEGEND

- | | |
|------------------------------------|---------------------------------|
| 1. Condenser Tank Access Door | 6. 2 Position Fan/Cooler Switch |
| 2. Condenser Air Intake Grill | 7. 2 Position High/Off Switch |
| 3. Condenser Hot Air Exhaust Grill | 8. Air Filter Slot |
| 4. 1" Handle | 9. Cold Air Supply Flange |
| 5. 2 Position On/Off Switch | 10. Return Air Grill |



ETL LISTED CONFORMS TO ANSI/UL1995
CERTIFIED TO CAN/CSA 22.2 NO 235

1-800-KWIKOOL

www.kwikool.com



SPECIFICATIONS

KAM1411

COOLING CAPACITY	BTU/hr @ 95F at 60% RH	13,700 (1.1-Ton)
COMPRESSOR DATA	Compressor Type	Hermetic Rotary
	Operating Temperatures	60-110 F 50%RH
	Refrigerant	410A
FAN DATA		
Evaporator	Fan Type (Centrifugal)	Direct Drive
	Air Flow (CFM)	30'-550 / 60'-495 / 90'-425
	Supply Air Device	1-6" diameter outlet
Condenser	Fan Type (Centrifugal)	Direct Drive
	Air Flow (CFM)	650
ELECTRICAL DATA	Power Supply (Volts)	115 Single Phase
	Current Consumption (Amps)	12.9
	Power Consumption (kW)	1.35
	Maximum Circuit Breaker (Amps)	20
	Recommended Breaker Size	15 or 20
	Minimum Circuit Ampacity(Amps)	19.575
	Min./Max. Voltage	105-125
	Power Cord Gauge/Length	12/50'
Plug Configuration	NEMA 5-15	
DIMENSIONAL DATA	Width x Depth x Height (Inches)	22" x 22" x 48"
	Weight (Lbs.)	205
	Shipping Weight (Lbs.)	280
	30' Duct & Storage Bag (Lbs.)	35
	Shipping Weight w/ 30' Duct & Storage Bag (Lbs.)	315
SAFETY DEVICE DATA	Compressor Overload	Internal
	Fan Motor Overload	Automatic Internal
	High Pressure Switch	Manual
	Compressor Short Cycle	Yes
	Automatic Restart	Yes
	Control	2 Position Switch Off-On
	Condensate Tank Overflow	Yes

1-800-KWIKOOL

www.kwikool.com