



LOADED WITH FEATURES THAT BENEFIT OWNER AND OPERATOR

NO PARTS OR DOWNTIME TO:

- Change fuel
- Confirm onsite voltage
- Manage heat output

TRULY PORTABLE

- Heavy-duty handle■ No-flat wheels
- Stackable

JOB SITE TOUGH

- Indoor/outdoor rated
- Rust resistant Tri-shield™ case

MORE THAN HEAT



Vent mode feature moves air like a fan



quicker troubleshooting

10-side case for easy inside-out access



Stackable



Stands on end



BOSS™ 1000 DF HEATER

BOSS™	1000 DF
BTU/H RATING	1,000,000
BLOWER FAN OUTPUT (CFM)	5,000
HEAT TYPE	DIRECT FIRED*
FUEL TYPE	DUAL FUEL — LP/NG
IGNITION TYPE	SPARK
FUEL CONSUMPTION LP GAS MIN./MAX. (LBS./HR.)	46.3
FUEL CONSUMPTION NAT. GAS MIN./MAX. (CU.FT./HR.)	1,000
INLET GAS PRESSURE LP MIN./MAX. (IN W.C.)	7"/13.5"
INLET GAS PRESSURE NG MIN./MAX. (IN W.C.)	7"/13.5"
AMPS (STARTING/CONTINUOUS OPERATION)	23.2/8.4
ELECTRIC SUPPLY (VOLTS/HZ/PHASE)	120/60/1
MOTOR HORSEPOWER	1 HP
LENGTH (IN.)	65 (WITH HANDLE)
WIDTH (IN.)	31
HEIGHT (IN.)	23.25
UNIT WEIGHT (LBS.)	300.0
BUILT-IN VOLT METER	YES
BUILT-IN THERMOSTAT	YES
VENT MODE	YES
DUCTABLE	NO
OMNI CERTIFIED U.S./CANADA	ANSI Z83.7-2017 / CSA 2.14-2017
* For use in self-ventilated area only.	TWO YEAR WARRANTY







WORLD PROVIDER OF INNOVATIVE HEATING SOLUTIONS