



NEW

COMMANDER™

MAKE-UP AIR UNITS

DF (LP/NG)

Benefits/Value:

- Constant air exchanges
- Modulating control reduces fuel costs
- Provides tempered fresh air
- Evenly heats interior and surfaces
- Maintains positive building pressure
- Available in 500,000 and 1,000,000 Btu/h

L.B. WHITE LINK™ L.B. White LINK™
 Now telematics-enabled to put critical alerts, runtime, location, and more at your fingertips.
 Learn more at LBWhite.com/LINK.



CA RESIDENTS:
 **WARNING**
 Cancer and reproductive harm. See www.P65Warnings.ca.gov.

INNOVATIVE CLIMATE SOLUTIONS

411 Mason Street, Onalaska, WI 54650
 (800) 345 7200
 (608) 783 5691
 (608) 783 6115, fax
www.lbwhite.com

© 2023 L.B. White Co.
 All rights reserved.
 All specifications are subject to change without notice.



MAKE-UP AIR	500K	1000K
BTU/HR rating (min/max)	100,000 - 500,000	200,000 - 1,000,000
Heated air output (CFM)	3000	6000
Fuel type	LP/NG	LP/NG
Connection	1" NPT	1" NPT
Fuel consumption LP gas max (lbs/hr)	5.51 Gal/Hr.	11.03 Gal/Hr.
Fuel consumption NG gas max (cu ft/hr)	500 CFH	1000 CFH
Amps	11.1	8.5
Electric supply (volts/hz/phase)	120 / 60 / 1	240 / 60 / 1
Electrical connection	Nema 5-20 120V, 20A 3-Wire	Nema L6-20 240V / 20A, 3-Wire
Diagnostic indicator	S	S
Unit length (in)	61.88	72.44
Unit width (in)	32.00	35
Unit height (in)	52.08	56.08
Shipping weight (lb)	525 lb	637 lb
Single point lifting bale	S	S
Thermostat connection	Customer Hard Wired	Customer Hard Wired
Fork pockets	A	A
Remote digital temperature control	A	A
Remote thermostat - dial	A	A
Ventilation (fan only)	S	S
Regulator	A	A
Outlet duct diameter (in)	16	24
Inlet duct diameter (in)	20	24
Max duct length (ft)	100	100
LINK™ Ready	S	S
Certified to ANSI 283.7 / CSA 2.14-2017	US / CAN	US Only

S=Standard A=Accessory

Accessories (sold separately):

- Thermostat (No cord included, customer supplied, hard wire into the heater), 500-09381
- Remote Digital Temp Control, 500-133951
- Kit, Duct, White, Flexible, 24" Dia x 25', w/clamp, 500-133767
- Kit, Duct, White, Flexible, 16" Dia x 25', w/clamp, 500-30076
- 2nd Stage Regulator (For 500K and 1M), 500-132136
- Forklift Pocket Kit (For 500K), 500-133940A
- Forklift Pocket Kit (For 1M), 500-133940B
- Kit, Duct, White, Flexible, 20" Dia x 25', w/clamp, 500-30053

CA RESIDENTS:



WARNING

Cancer and reproductive harm. See
www.P65Warnings.ca.gov.