Macurco Building & Home Solutions

Whether you are looking for gas detection for a security system, building automation or HVAC system, for personal safety or for monitoring specific gases in potentially hazardous environments, Macurco has a gas detector to meet your needs.



The Macurco controller family has various options to meet your facility's needs. In conjunction with Macurco gas detectors, these controllers provide automatic control to help maintain an acceptable environment in parking garages or other applications. These systems easily configure, making installation hassle-free. The control panel series are designed to meet specifications for safety in enclosed parking garages, including the Uniform Building Code and OSHA 50ppm CO requirements. With multiple control panel options Macurco will help you find



Key Features

DVP-120 (Analog)

DVP Family

DVP-120M (Digital)

DVP-120B/ DVP-120C (Digital w/ BACnet output)

• DVP-120: 12 analog (4-20mA) sensor connections

 DVP-120M: 87 digital sensor connections (RS-485) + 12 analog (4-20mA) sensor connections

Control Panels

Detection Ventilation Control Panels

the suitable controller for your specific application.

- Three 10A SPDT fan/alarm relays
- Two 24VDC drivers for horn/strobe
- Compatible with Macurco 6-Series
- · Auto recognizes Macurco detectors
- Settings are customizable, default is per OSHA
- DVP-120B: BACnet MSTP output
- DVP-120C: Title 24 compliant (CO & NO₂ only)

Applications

- Parking garages
- Car dealerships
- Ambulance/fire house bays
- Warehouses
- Manufacturing
- Loading docks
- Mechanical rooms
- Distribution centers
- Vehicle repair facilities
- Bus depots

Control Panels



Specifications

Size	10.5" x 12.5" x 2." (10.5 X 37.75 X 5.08 cm)
Weight	6.5 lbs (2.9 kg)
Voltage/Current	Power Input: 90 – 250 VAC,
	1 Amp, 47 – 63 Hz, single phase
Operating Temperature	32°F to 120°F (0°C to 49°C)
Ambient Humidity	0% to 90% RH non-condensing
Display	LCD display: 2 rows of 16 characters
	with backlight
Mounting	Mounting holes in each corner
Relays	Three 10A, 240 VAC SPDT fan/alarm relays
Settings	External keypad for user selection of the
	transducer/alarm display and setting the
	configuration
Status Indicators	(LED): Power, ALARM/warning, hush,
	Relay 1, Relay 2 & Relay 3
Alarms	Drivers for external Horn and Strobe, externally
	visible system, alarm and relay status indicators
Enclosure	Lockable NEMA 1 type enclosure
Certifications	ETL Listed to UL 2017
	CAN/CSA-C22.2 No.
	14-13, LADBS Approved (DVP-120, DVP-120C)
Warranty	Two Year Limited Warranty

Models

Description	Model Number
BACnet - 99 Digital Connections	DVP-120B
BACnet - 99 Digital Connections	DVP-120C (CO & NO ₂ detectors only)
87 Addressable Connections	DVP-120M
12 Analog Connections	DVP-120

Accessories

Name	Model Number
Addressable Adapter (6 series only)	MRS-485
Horn and Strobe (5 color options)	HS-A, HS-B, HS-R, HS-C
Power Supply	MAC6AMP-4, MAC10AMP-1, MAC10AMP-4



Control Panel Layouts





Since 1972 Macurco has been providing gas detection solutions for various applications. Macurco provides the highest quality gas detection solutions to customers worldwide.



Macurco Inc.

1504 W. 51st Street Sioux Falls, SD 57105

Phone: 1-877-367-7891 Website: www.macurco.com Email: info@macurco.com